Topsfield, Vanceboro, Waite, Talmage, Lambert Lake TWP Indian TWP and Codyville Plt.

PIN 011007.30 PIN 011269.00 PIN 011475.00

BEFORE SUBMITTING YOUR BID

- 1. Use pen and ink to complete the Bid.
- 2. Have you signed and completed the Contract Agreement, Offer & Award Forms?
- 3. As a minimum, the Bidder will submit a Bid Package consisting of the Notice to Contractors, the completed Acknowledgement of Bid Amendments & Submission of Bid Bond Validation Number form, the completed Schedule of Items, 2 copies of the completed Agreement, Offer, & Award form, a Bid Bond or Bid Guarantee, and any other Certifications or Bid Requirements listed in the Bid Book.
- 4. Have you included prices for all Bid Items? ("Zero is not considered a bid price.")
- 5. Have you included a bid guarantee? Acceptable forms are:
 - A. Bid Bond on the Department's prescribed form for 5% of the Bid Amount. (Or forms that do not contain any significant variations from the Department's forms as solely determined by the Department.)
 - B. Official Bank Check, Cashier's Check, Certified Check, U.S. Postal Money Order or Negotiable Certificate of Deposit in the amount stated in the Notice to Contractors.
- 6. If the written Bid is to be sent, Federal Express overnight delivery is suggested as the package is delivered directly to the DOT Headquarters Building in Augusta. Other means, such as U.S. Postal Services' Express Mail has proven not to be reliable.

AND FOR FEDERAL AID PROJECTS

7. Have you included your DBE Utilization commitment in the proper amounts and signed the DBE Certification?

If you need further information regarding Bid preparation, call the DOT Contracts Section at (207)624-3430.

For complete specifications regarding bidding requirements, refer to Section 102 of the Maine Department of Transportation, Standard Specifications, Revision December 2002.

NOTICE

The Maine Department of Transportation is attempting to improve the way Bid Amendments/Addendums are handled, and allow for an electronic downloading of bid packages from our website, while continuing to maintain a planholders list.

Prospective bidders, subcontractors or suppliers who wish to download a copy of the bid package and receive a courtesy notification of project specific bid amendments, must provide an email address to Diane Barnes at the MDOT Contracts mailbox at:

MDOT.contracts@maine.gov. Each bid package will require a separate request. Please provide us an email address, so we can maintain the planholders list that both the industry and MDOT uses.

Additionally, the new Acknowledgement of Bid Amendment form will be placed in MDOT bid packages beginning with the 2/12/03 advertisements. After that date, interested parties will be responsible for reviewing and retrieving the Bid Amendments from our web site, and acknowledging receipt and incorporating those Bid Amendments in their bids.

The downloading of bid packages from the MDOT website is <u>not</u> the same as providing an electronic bid to the Department. Electronic bids must be submitted via http://www.BIDX.com. For information on electronic bidding contract Rebecca Pooler at rebecca.pooler@maine.gov.

STATE OF MAINE DEPARTMENT OF TRANSPORTATION

Bid Guaranty-Bid Bond Form

KNOW ALL MEN BY THESE PRESEN	NTS THAT	
, of the	: City/Town of	and State of
as Principal, and		as Surety, a
Corporation duly organized under the laws	of the State of	and having a usual place of
Business in	and hereby held	and firmly bound unto the Treasurer of
the State of Maine in the sum of	,for p	ayment which Principal and Surety bind
themselves, their heirs, executers, administ		
The condition of this obligation is that the	Principal has submi	itted to the Maine Department of
Transportation, hereafter Department, a cer	rtain bid, attached h	nereto and incorporated as a
part herein, to enter into a written contract	for the construction	ı of
	and if the	he Department shall accept said bid
and the Principal shall execute and deliver	a contract in the for	rm attached hereto (properly
completed in accordance with said bid) and	l shall furnish bond	s for this faithful performance of
said contract, and for the payment of all pe	rsons performing la	ubor or furnishing material in
connection therewith, and shall in all other	respects perform th	ne agreement created by the
acceptance of said bid, then this obligation	shall be null and ve	oid; otherwise it shall remain in full
force, and effect.		
Signed	and sealed this	day of20
WITNESS:		PRINCIPAL:
		By
		By:
		By:
WITNESS		SURETY: By
		Ву:
	_	Name of Local Agency:

NOTICE

For security and other reasons, all Bid Packages which are mailed, shall be provided in double (one envelope inside the other) envelopes. The *Inner Envelope* shall have the following information provided on it:

Bid Enclosed - Do Not Open

PIN:

Town:

Date of Bid Opening:

Name of Contractor with mailing address and telephone number:

In Addition to the usual address information, the *Outer Envelope* should have written or typed on it:

Double Envelope: Bid Enclosed

PIN:

Town:

Date of Bid Opening:

Name of Contractor:

This should not be much of a change for those of you who use Federal Express or similar services.

Hand-carried Bids may be in one envelope as before, and should be marked with the following infrormation:

Bid Enclosed: Do Not Open

PIN:

Town:

Name of Contractor:

INSTRUCTIONS FOR PREPARING THE CONTRACTOR'S DISADVANTAGED BUSINESS ENTERPRISE UTILIZATION PLAN

The Contractor Shall:

- 1. Submit a completed <u>Contractor's Disadvantaged Business</u> <u>Enterprise Utilization Plan</u> to the Contract's Engineer by 4:30 P.M. on the Bid day.
- 2. Extend equal opportunity to MDOT certified DBE firms (as listed in MDOT's DBE Directory of Certified Businesses) in the selection and utilization of Subcontractors and Suppliers.

SPECIFIC INSTRUCTIONS FOR COMPLETING THE FORM:

Insert Contractor name, the name of the person(s) preparing the form, and that person(s) telephone and fax number.

Provide total Bid price, Federal Project Identification Number, and location of the Project work.

In the columns, name each DBE firm to be used, provide the Unit or Item cost of the Work/Product to be provided by the DBE firm, give a brief description of the Work, and the dollar value of the Work.

If no DBE firm is to be utilized, the Contractor must document the reason(s) why no DBE firms are being used. Specific supporting evidence of good faith efforts taken by Contractors to solicit DBE Bidders must be attached. This evidence, as a minimum, includes phone logs, e-mail and/or mail DBE solicitation records, and the documented results of these solicitations.

NOTICE

The Department has revised the <u>Disadvantaged Business</u> <u>Enterprise Proposed Utilization</u> form and the procedure that has been used for the past several months for Contractors to submit the form.

The Apparent Low Bidder now must submit the form by close of Business (4:30 P.M.) on Bid day.

The new <u>Contractor's Disadvantaged Business Enterprise</u> <u>Proposed Utilization Plan</u> form contains additional information that is required by USDOT.

The <u>Disadvantaged Business Enterprise Proposed Utilization</u>
<u>Plan</u> form will no longer be used. The new <u>Contractor's</u>
<u>Disadvantaged Business Enterprise Proposed Utilization Plan</u>
form must be used.

A copy of the new <u>Contractor's Disadvantaged Business</u> <u>Enterprise Proposed Utilization Plan</u> and instructions for completing it are attached.

Note: Questions about DBE firms, or to obtain a printed copy of the DBE Directory, contact Equal Opportunity at (207) 624-3066.

MDOTs DBE Directory of Certified firms can also be obtained at http://www.state.me.us/mdot/humnres/o_equalo/cdwbed_h.htm

NOTICE

Bidders:

Please use the attached "Request for Information" form when faxing questions and comments concerning specific Contracts that have been Advertised for Bid. Include additional numbered pages as required.

State of Maine Department of Transportation


REQUEST FOR INFORMATION

Date _		Time					
Information Requested:	PIN:						
		Phone: ()					
		the number listed in the Notice					
Response:							
Response By:		Date:					

CONTRACTOR'S DISADVANTAGED BUSINESS ENTERPRISE PROPOSED UTILIZATION PLAN

Low Bidder shall furnish completed form to Contracts Section by 4:30 P.M. on Bid Opening day.

то:	: MDOT Contracts Section 16 State House Station, Augusta, Me 04333-0016 or Fax: 207-624-3431			Contractor: Prepared by: Telephone:Fax:					
BID J	PRICE: \$	FEDERAI	. PROJECT	Γ#	_LOCATION: _				
Т	OTAL DBE PAR	RTICIPATION A	S A PERCI	ENT OF TOTA	AL BID PRICE =	%			
	DBE Firm*	Unit/Item Cost	Unit #		tion of work & m Number	Actual \$ Value			
If no DBE firm(s) are used, bidder must document efforts made to secure DBE participation and attach supporting evidence of this effort: Examples: Bidder relies wholly upon low quote subcontractor section, DBE firm(s) were not low quote. No DBE firms bid. *Only DBE firms certified by MDOT prior to bidding can be utilized by Contractor for DBE credit. Directory of certified DBEs is available on MDOT's website: www.state.me.us/mdot									
•	l Opportunity Use:			Act	tion:				



MAINE DEPARTMENT OF TRANSPORTATION

Certified Disadvantaged and Women Business Enterprise

DBE DIRECTORY - MINORITY OWNED

WBE DIRECTORY - WOMEN OWNED

WEBSITE FOR DIRECTORY CAN BE FOUND AT: http://www.state.me.us/mdot/humnres/o equalo/cdwbed h.htm

It is the responsibility of the Contractor to access the DBE Directory at this site in order to have the most current listings.

STATE OF MAINE DEPARTMENT OF TRANSPORTATION NOTICE TO CONTRACTORS

Sealed Bids addressed to the Maine Department of Transportation, Augusta, Maine 04333 and endorsed on the wrapper "Bid for Milling, Hot Mix Asphalt Overlay, Hot Maintenance Mulch and Strut Replacement in the towns of Topsfield, Vanceboro, Waite and Talmage, the townships of Lambert Lake and Indian TWP-Passamaquoddy Indian Reservation and plantation of Codyville" will be received from contractors at the Reception Desk, Maine DOT Building, Child Street, Augusta, Maine, until 11:00 o'clock A.M. (prevailing time) on January 7, 2004, and at that time and place publicly opened and read. Bids will be accepted from contractors prequalified by the Department of Transportation for highway construction or paving projects. All other Bids may be rejected. MDOT provides the option of electronic bidding. We accept electronic bids for those bid packages posted on the bidx.com website. Electronic bids do not have to be accompanied by paper bids. Please note: the Department will accept a facsimile of the bid bond; however, the original bid bond must then be received at the MDOT Contract Section within 72 hours of the bid opening. Until further notice, dual bids (one paper, one electronic) will be accepted, with the paper copy taking precedence.

Description: Maine Federal Aid Project No. 11007.30, PIN 011007.30; STP-1126(900)X, PIN 11269.00; 11475.00, PIN 011475.00

Location: In Washington County, project 11007.30 is located on Route 6, beginning at Route 1 and extending easterly 22 miles to the US - Canada border. Project STP-1126(900)X is located on Route 1, beginning 1.41 miles southerly of the Waite town line and extending northerly 7.75 miles to the Topsfield town line. Project 11475.00 - Culvert Replacement: is located on Route 6, 0.44 of a mile easterly of Route 1.

Outline of Work: Milling, ¼ Hot Mix Asphalt Overlay, Hot Maintenance Mulch, Strut Replacement and other incidental work.

The basis of award will be the total of all sections

For general information regarding Bidding and Contracting procedures, contact Bruce Carter at (207)624-3430. Our webpage at http://www.state.me.us/mdot/project/design/homepg.htm contains a copy of the schedule of items, Plan Holders List, written portions of bid amendments (not drawings), and bid results. For Project-specific information fax all questions to **Jamie Andrews** at (207)624-3401. Questions received after 12:00 noon of Monday prior to bid date will not be answered. Bidders shall not contact any other Departmental staff for clarification of Contract provisions, and the Department will not be responsible for any interpretations so obtained. Hearing impaired persons may call the Telecommunication Device for the Deaf at (207)287-3392.

Specifications and bid forms may be seen at the Maine DOT Building in Augusta, Maine and at the Department of Transportation's Division Office in Ellsworth. They may be purchased from the Department between the hours of 8:00 a.m. to 4:30 p.m. by cash, credit card (Visa/Mastercard) or check payable to Treasurer, State of Maine sent to Maine Department of Transportation, Attn.: Mailroom, 16 State House Station, Augusta, Maine 04333-0016. They also may be purchased by telephone at (207)624-3536 between the hours of 8:00 a.m. to 4:30 p.m. Bid Book \$10 (\$13 by mail), Single Sheets \$2, payment in advance, all non-refundable.

Each Bid must be made upon blank forms provided by the Department and must be accompanied by a bid bond at 5% of the bid amount or an official bank check, cashier's check, certified check, certificate of deposit, or United States postal money order in the amount of \$40,000 payable to Treasurer, State of Maine as a Bid guarantee. A Contract Performance Surety Bond and a Contract Payment Surety Bond, each in the amount of 100 percent of the Contract price, will be required of the successful Bidder.

This Contract is subject to all applicable Federal Laws. This contract is subject to compliance with the Disadvantaged Business Enterprise program requirements as set forth by the Maine Department of Transportation.

All work shall be governed by "State of Maine, Department of Transportation, Standard Specifications, Revision of December 2002", price \$10 [\$13 by mail], and Standard Details, Revision of December 2002, price \$20 [\$25 by mail] Standard Detail updates can be found at http://www.state.me.us/mdot/project/design/homepg.htm

The right is hereby reserved to the MDOT to reject any or all Bids.

Augusta, Maine December 17, 2003 DORITY No. 2093

JOHN E. DORITY CHIEF ENGINEER Topsfield, Vanceboro, Waite and Talmage, the townships of Lambert Lake and Indian TWP-Passamaquoddy Indian
Reservation and plantation of Codyville
PINS 011007.30, 011269.00, 011475.00
October 29, 2003
Supercedes June 26, 2003

SPECIAL PROVISION 102.7.3 ACKNOWLEDGMENT OF BID AMENDMENTS & SUBMISSION OF BID BOND VALIDATION NUMBER (IF APPLICABLE)

With this form, the Bidder acknowledges its responsibility to check for all Amendments to the Bid Package. For each Project under Advertisement, Amendments are located at http://www.state.me.us/mdot/comprehensive-list-projects/project-information.php It is the responsibility of the Bidder to determine if there are Amendments to the Project, to download them, and to incorporate them into their Bid Package. The Maine DOT will not post Bid Amendments any later than noon the day before Bid opening.

Amendment Number	Date

The Contractor, for itself, its successors and assigns, hereby acknowledges that it has received all of the above referenced Amendments to the Bid Package. Failure to acknowledge receipt of all Amendments to the Bid Package will be considered a Non-curable Bid Defect in accordance with Section 102.11.1 of the Standard Specifications, Revision of December 2002.

CONTRACTOR

Date	Signature of authorized representative
	(Name and Title Printed)

MAINE DEPARTMENT OF TRANSPORTATION

BID

DATE OF OPENING: CALL ORDER:

CONTRACT ID : 011269.00

PROJECTS

011007.30 STP-1126(900)X 011475.00

COUNTY : WASHINGTON

MAINE DEPARTMENT OF TRANSPORTATION PAGE: 1 DATE: 031211

SCHEDULE OF ITEMS

REVISED:

CONTRACT ID: 011269.00 PROJECT(S): 011007.30

STP-1126(900)X

011475.00

CONTRA	ACTOR :			
LINE	<u> </u>	APPROX.	UNIT PRICE	BID AMOUNT
NO	DESCRIPTION	QUANTITY AND UNITS	DOLLARS CTS	DOLLARS CTS
SECTIO	ON 0001 HIGHWAY ITEMS			
	202.202 REMOVING PAVEMENT SURFACE 	 102656.000 SY		
0020	304.104 AGGREGATE SUBBASE COURSE (PLAN QUANTITY)	 100.000 CY		
	403.207 HOT MIX ASPHALT 19.0 MM HMA 	 65.000 T		
	403.210 HOT MIX ASPHALT 9.5 MM HMA 	 7635.700 T	 	
	409.15 BITUMINOUS TACK COAT APPLIED 	 2053.100 G		
0060	461.210 MAINTENANCE SURFACE TREATMENT - 9.5 MM	 11000.000 T		
0070	603.47 60 INCH REINFORCED CONCRETE PIPE CLASS IV	 112.000 LF		
0080	610.08 PLAIN RIPRAP 	 25.000 CY		
0090	620.58 EROSION CONTROL GEOTEXTILE 	 140.000 SY		

MAINE DEPARTMENT OF TRANSPORTATION PAGE: 2 DATE: 031211

SCHEDULE OF ITEMS REVISED:

CONTRACT ID: 011269.00 PROJECT(S): 011007.30

STP-1126(900)X 011475.00

LINE NO	TTEM DESCRIPTION	APPROX.	UNIT PRI	CE	BID AMOUNT		
INO	DESCRIPTION	AND UNITS	l		DOLLARS	CTS	
0100	627.811 TEMPORARY BI-DIRECTIONAL YELLOW DELINEATORS	 1640.000 EA					
	629.05 HAND LABOR, STRAIGHT TIME 	 95.000 HR	 		 	 	
	631.12 ALL PURPOSE EXCAVATOR (INCLUDING OPERATOR)	 65.000 HR	 		 	 	
	631.172 TRUCK - LARGE (INCLUDING OPERATOR)	 130.000 HR	 		 		
0140	639.19 FIELD OFFICE TYPE B 	1.000 EA	 		 		
	652.39 WORK ZONE TRAFFIC CONTROL 	 LUMP 	LUMP				
0160	656.75 TEMPORARY SOIL EROSION AND WATER POLLUTION CONTROL	 LUMP 	 LUMP		 		
0170	659.10 MOBILIZATION 	 LUMP 	 LUMP		 		
	 SECTION 0001 TOTAL		 				
	 TOTAL BID		 				

CONTRACT AGREEMENT, OFFER & AWARD

AGREEMENT made on the date last signed below, by and between the State of Maine, acting through and by its Department of Transportation (Department), an agency of state government with its principal administrative offices located at Child Street, Augusta, Maine, with a mailing address at 16 State House Station, Augusta, Maine 04333-0016, and

a corporation of	or other	legal	entity	organized	under	the	laws	of	the	State	of	Maine,	with	its
principal place	of busin	ess lo	cated	at										

The Department and the Contractor, in consideration of the mutual promises set forth in this Agreement (the "Contract"), hereby agree as follows:

A. The Work.

The Contractor agrees to complete all Work as specified or indicated in the Contract including Extra Work in conformity with the Contract, PIN No. 011007.30, 11269.00 and 011475.00 for the Milling, ³/₄ Hot Mix Asphalt Overlay, Hot Maintenance Mulch and Strut Replacement in the towns of Topsfield, Vanceboro, Waite and Talmage, the townships of Lambert Lake and Indian TWP-Passamaquoddy Indian Reservation and plantation of Codyville, County of Washington, Maine. The Work includes construction, maintenance during construction, warranty as provided in the Contract, and other incidental work.

The Contractor shall be responsible for furnishing all supervision, labor, equipment, tools supplies, permanent materials and temporary materials required to perform the Work including construction quality control including inspection, testing and documentation, all required documentation at the conclusion of the project, warranting its work and performing all other work indicated in the Contract.

The Department shall have the right to alter the nature and extent of the Work as provided in the Contract; payment to be made as provided in the same.

B. Time.

The Contractor agrees to complete all Work, except warranty work, on or before September 4, 2004. Further, the Department may deduct from moneys otherwise due the Contractor, not as a penalty, but as Liquidated Damages in accordance with Sections 107.7 and 107.8 of the State of Maine Department of Transportation Standard Specifications, Revision of December 2002.

C. Price.

The quantities give	n in the Schedule of Items of the Bid Package will be used as the
basis for determini	ng the original Contract amount and for determining the amounts of
the required Perfor of this offer is	mance Surety Bond and Payment Surety Bond, and that the amount
\$	Performance Bond and Payment Bond each being
100% of the amour	t of this Contract.

D. Contract.

This Contract, which may be amended, modified, or supplemented in writing only, consists of the Contract documents as defined in the Plans, Standard Specifications, Revision of December 2002, Standard Details Revision of December 2002 as updated through advertisement, Supplemental Specifications, Special Provisions, Contract Agreement; and Contract Bonds. It is agreed and understood that this Contract will be governed by the documents listed above.

E. Certifications.

By signing below, the Contractor hereby certifies that to the best of the Contractor's knowledge and belief:

- 1. All of the statements, representations, covenants, and/or certifications required or set forth in the Bid and the Bid Documents, including those in Appendix A to Division 100 of the Standard Specifications Revision of December 2002 (Federal Contract Provisions Supplement), and the Contract are still complete and accurate as of the date of this Agreement.
- 2. The Contractor knows of no legal, contractual, or financial impediment to entering into this Contract.
- 3. The person signing below is legally authorized by the Contractor to sign this Contract on behalf of the Contractor and to legally bind the Contractor to the terms of the Contract.

F. Offer.

The undersigned, having carefully examined the site of work, the Plans, Standard Specifications Revision of December 2002, Standard Details Revision of December 2002 as updated through advertisement, Supplemental Specifications, Special Provisions, Contract Agreement; and Contract Bonds contained herein for construction of: PIN No. 011007.30, 11269.00 and 011475.00 for the Milling, ¾ Hot Mix Asphalt Overlay, Hot Maintenance Mulch and Strut Replacement in the towns of Topsfield, Vanceboro, Waite and Talmage, the townships of Lambert Lake and Indian TWP-Passamaquoddy Indian Reservation and plantation of Codyville, County of Washington, State of Maine, on which bids will be received until the time specified in the "Notice to Contractors" do(es) hereby bid and offer to enter into this contract to supply all the materials, tools, equipment and labor to construct the whole of the Work in strict accordance with the terms and conditions of this Contract at the unit prices in the attached "Schedule of Items".

The Offeror agrees to perform the work required at the price specified above and in accordance with the bids provided in the attached "Schedule of Items" in strict accordance with the terms of this solicitation, and to provide the appropriate insurance and bonds if this offer is accepted by the Government in writing.

As Offeror also agrees:

First: To do any extra work, not covered by the attached "Schedule of Items", which may be ordered by the Resident, and to accept as full compensation the amount determined upon a "Force Account" basis as provided in the Standard Specifications, Revision of December 2002, and as addressed in the contract documents.

Second: That the bid bond at 5% of the bid amount or the official bank check, cashier's check, certificate of deposit or U. S. Postal Money Order in the amount given in the "Notice to Contractors", payable to the Treasurer of the State of Maine and accompanying this bid, shall be forfeited, as liquidated damages, if in case this bid is accepted, and the undersigned shall fail to abide by the terms and conditions of the offer and fail to furnish satisfactory insurance and Contract bonds under the conditions stipulated in the Specifications within 15 days of notice of intent to award the contract.

Third: To begin the Work on the date specified in the Engineer's "Notice to Commence Work" as stated in Section 107.2 of the Standard Specifications Revision of December 2002 and complete the Work within the time limits given in the Special Provisions of this Contract.

Fourth: The Contractor will be bound to the Disadvantaged Business Enterprise (DBE) Requirements contained in the attached Notice (Additional Instructions to Bidders) and submit a completed Contractor's Disadvantaged Business Enterprise Utilization Plan by 4:30pm on the day of bid opening to the Contracts Engineer.

Fifth: That this offer shall remain open for 30 calendar days after the date of opening of bids.

Sixth: The Bidder hereby certifies, to the best of its knowledge and belief that: the Bidder has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of competitive bidding in connection with its bid, and its subsequent contract with the Department.

IN WITNESS WHEREOF, the Contractor, for itself, its successors and assigns, hereby execute two duplicate originals of this Agreement and thereby binds itself to all covenants, terms, and obligations contained in the Contract Documents.

		CONTRACTOR
Date		(Signature of Legally Authorized Representative of the Contractor)
	Witness	(Name and Title Printed)
G.	Award. Your offer is hereby accepted.	This award consummates the Contract, and the
	documents referenced herein.	MAINE DEPARTMENT OF TRANSPORTATION
	Date	By: David A. Cole, Commissioner
	Witness	

CONTRACT AGREEMENT, OFFER & AWARD

AGREEMENT made on the date last signed below, by and between the State of Maine, acting through and by its Department of Transportation (Department), an agency of state government with its principal administrative offices located at Child Street, Augusta, Maine, with a mailing address at 16 State House Station, Augusta, Maine 04333-0016, and

a corporation of	or other	legal	entity	organized	under	the	laws	of	the	State	of	Maine,	with	its
principal place	of busin	ess lo	cated	at										

The Department and the Contractor, in consideration of the mutual promises set forth in this Agreement (the "Contract"), hereby agree as follows:

A. The Work.

The Contractor agrees to complete all Work as specified or indicated in the Contract including Extra Work in conformity with the Contract, PIN No. 011007.30, 11269.00 and 011475.00 for the Milling, ³/₄ Hot Mix Asphalt Overlay, Hot Maintenance Mulch and Strut Replacement in the towns of Topsfield, Vanceboro, Waite and Talmage, the townships of Lambert Lake and Indian TWP-Passamaquoddy Indian Reservation and plantation of Codyville, County of Washington, Maine. The Work includes construction, maintenance during construction, warranty as provided in the Contract, and other incidental work.

The Contractor shall be responsible for furnishing all supervision, labor, equipment, tools supplies, permanent materials and temporary materials required to perform the Work including construction quality control including inspection, testing and documentation, all required documentation at the conclusion of the project, warranting its work and performing all other work indicated in the Contract.

The Department shall have the right to alter the nature and extent of the Work as provided in the Contract; payment to be made as provided in the same.

B. Time.

The Contractor agrees to complete all Work, except warranty work, on or before September 4, 2004. Further, the Department may deduct from moneys otherwise due the Contractor, not as a penalty, but as Liquidated Damages in accordance with Sections 107.7 and 107.8 of the State of Maine Department of Transportation Standard Specifications, Revision of December 2002.

C. Price.

The quantities give	n in the Schedule of Items of the Bid Package will be used as the
basis for determini	ng the original Contract amount and for determining the amounts of
the required Perfor of this offer is	mance Surety Bond and Payment Surety Bond, and that the amount
\$	Performance Bond and Payment Bond each being
100% of the amour	t of this Contract.

D. Contract.

This Contract, which may be amended, modified, or supplemented in writing only, consists of the Contract documents as defined in the Plans, Standard Specifications, Revision of December 2002, Standard Details Revision of December 2002 as updated through advertisement, Supplemental Specifications, Special Provisions, Contract Agreement; and Contract Bonds. It is agreed and understood that this Contract will be governed by the documents listed above.

E. Certifications.

By signing below, the Contractor hereby certifies that to the best of the Contractor's knowledge and belief:

- 1. All of the statements, representations, covenants, and/or certifications required or set forth in the Bid and the Bid Documents, including those in Appendix A to Division 100 of the Standard Specifications Revision of December 2002 (Federal Contract Provisions Supplement), and the Contract are still complete and accurate as of the date of this Agreement.
- 2. The Contractor knows of no legal, contractual, or financial impediment to entering into this Contract.
- 3. The person signing below is legally authorized by the Contractor to sign this Contract on behalf of the Contractor and to legally bind the Contractor to the terms of the Contract.

F. Offer.

The undersigned, having carefully examined the site of work, the Plans, Standard Specifications Revision of December 2002, Standard Details Revision of December 2002 as updated through advertisement, Supplemental Specifications, Special Provisions, Contract Agreement; and Contract Bonds contained herein for construction of: PIN No. 011007.30, 11269.00 and 011475.00 for the Milling, ¾ Hot Mix Asphalt Overlay, Hot Maintenance Mulch and Strut Replacement in the towns of Topsfield, Vanceboro, Waite and Talmage, the townships of Lambert Lake and Indian TWP-Passamaquoddy Indian Reservation and plantation of Codyville, County of Washington, State of Maine, on which bids will be received until the time specified in the "Notice to Contractors" do(es) hereby bid and offer to enter into this contract to supply all the materials, tools, equipment and labor to construct the whole of the Work in strict accordance with the terms and conditions of this Contract at the unit prices in the attached "Schedule of Items".

The Offeror agrees to perform the work required at the price specified above and in accordance with the bids provided in the attached "Schedule of Items" in strict accordance with the terms of this solicitation, and to provide the appropriate insurance and bonds if this offer is accepted by the Government in writing.

As Offeror also agrees:

First: To do any extra work, not covered by the attached "Schedule of Items", which may be ordered by the Resident, and to accept as full compensation the amount determined upon a "Force Account" basis as provided in the Standard Specifications, Revision of December 2002, and as addressed in the contract documents.

Second: That the bid bond at 5% of the bid amount or the official bank check, cashier's check, certificate of deposit or U. S. Postal Money Order in the amount given in the "Notice to Contractors", payable to the Treasurer of the State of Maine and accompanying this bid, shall be forfeited, as liquidated damages, if in case this bid is accepted, and the undersigned shall fail to abide by the terms and conditions of the offer and fail to furnish satisfactory insurance and Contract bonds under the conditions stipulated in the Specifications within 15 days of notice of intent to award the contract.

Third: To begin the Work on the date specified in the Engineer's "Notice to Commence Work" as stated in Section 107.2 of the Standard Specifications Revision of December 2002 and complete the Work within the time limits given in the Special Provisions of this Contract.

Fourth: The Contractor will be bound to the Disadvantaged Business Enterprise (DBE) Requirements contained in the attached Notice (Additional Instructions to Bidders) and submit a completed Contractor's Disadvantaged Business Enterprise Utilization Plan by 4:30pm on the day of bid opening to the Contracts Engineer.

Fifth: That this offer shall remain open for 30 calendar days after the date of opening of bids.

Sixth: The Bidder hereby certifies, to the best of its knowledge and belief that: the Bidder has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of competitive bidding in connection with its bid, and its subsequent contract with the Department.

IN WITNESS WHEREOF, the Contractor, for itself, its successors and assigns, hereby execute two duplicate originals of this Agreement and thereby binds itself to all covenants, terms, and obligations contained in the Contract Documents.

		CONTRACTOR	
Date		(Signature of Legally Authorized Representativ of the Contractor)	
	Witness	(Name and Title Printed)	
G.	Award. Your offer is hereby accepted.	This award consummates the Contract, and the	
	documents referenced herein.	MAINE DEPARTMENT OF TRANSPORTATION	
	Date	By: David A. Cole, Commissioner	
	Witness		

CONTRACT AGREEMENT, OFFER & AWARD

AGREEMENT made on the date last signed below, by and between the State of M	aine,				
acting through and by its Department of Transportation (Department), an agency of	state				
government with its principal administrative offices located at 1705 U.S. Route	202,				
Winthrop, Maine, with a mailing address at 16 State House Station, Augusta, Maine 04	1333-				
0016, and(Name of the firm bidding the job)					
a corporation or other legal entity organized under the laws of the State of Maine, wi	th its				
principal place of business located at(address of the firm bidding the job)					
	•				
The Department and the Contractor, in consideration of the mutual promises set forth in	- n this				
Agreement (the "Contract"), hereby agree as follows:					
A. The Work.					
The Contractor agrees to complete all Work as specified or indicated in the Con	ntract				
including Extra Work in conformity with the Contract, PIN No. 1224.00	rer ere e				
molecules 2 x m 1 your in community white the community with the commu	for				
the Hot Mix Asphalt Overlay in	the				
town/city of West Eastport \ , County					
Washington , Maine. The Work includes construction, maintenance d					
construction, wateranty as provided in the Contract, and other incidental work.					
The Contractor shall be responsible for furnishing all supervision, labor, equip	nent.				
tools supplies, permanent materials and temporary materials required to perform					
Work including construction quality control including inspection, testing					
documentation, all required documentation at the conclusion of the project, warranting					
its work and performing all other work indicated in the Contract.	mung				
The Department shall have the right to alter the nature and extent of the Wo	rk as				
provided in the Contract; payment to be made as provided in the same.					
B. Time.					
The Contractor agrees to complete all Work, except warranty work, on or b	efore				
November 15, 2003. Further, the Department may deduct from moneys other					
due the Contractor, not as a penalty, but as Liquidated Damages in accordance					
Sections 107.7 and 107.8 of the State of Maine Department of Transportation State					
Specifications, Revision of December 2002.					

C. Price.

The quantities given in the Schedule of Items of the Bid Package will be used as the basis for determining the original Contract amount and for determining the amounts of the required Performance Surety Bond and Payment Surety Bond, and that the amount of this offer is _____(Place bid here in alphabetical form such as One Hundred and

Two dollars and 10 cents)

\$_ (repeat bid here in numerical terms, such as \$102.10) \ Performance

Bond and Payment Bond each being 100% of the amount of this Contract.

D. Contract.

This Contract, which may be amended, modified, or supplemented in writing only, consists of the Contract documents as defined in the Plans, Standard Specifications, Revision of December 2002, Standard Detalls Revision of December 2002, Supplemental Specifications, Special Provisions, Contract Agreement; and Contract Bonds. It is agreed and understood that this Contract will be governed by the documents listed above.

E. Certifications.

By signing below, the Contractor hereby certifies that to the best of the Contractor's knowledge and belief:

- 1. All of the statements representations, covenants, and/or certifications required or set forth in the Bid and the Bid Documents, including those in Appendix A to Division 100 of the Standard Specifications Revision of December 2002 (Federal Contract Provisions Supplement), and the Contract are still complete and accurate as of the date of this Agreement.
- 2. The Contractor knows of no legal, contractual, or financial impediment to entering into this Contract.
- 3. The person signing below is legally authorized by the Contractor to sign this Contract on behalf of the Contractor and to legally bind the Contractor to the terms of the Contract.

F. Offer.

The undersigned, having carefully examined the site of work, the Plans, Standard Specifications, Revision of December 2002, Standard Details Revision of December 2002, Supplemental Specifications, Special Provisions, Contract Agreement; and Contract Bonds contained herein for construction of:

PIN 1234.00 West Eastport, Hot Mix Asphalt Overlay

State of Maine, on which bids will be received until the time specified in the "Notice to Contractors" do(es) hereby bid and offer to enter into this contract to supply all the materials, tools, equipment and labor to construct the whole of the Work in strict accordance with the terms and conditions of this Contract at the unit prices in the attached "Schedule of Items".

The Offeror agrees to perform the work required at the price specified above and in accordance with the bids provided in the attacked "Schedule of Items" in strict accordance with the terms of this solicitation, and to provide the appropriate insurance and bonds if this offer is accepted by the Government in writing.

As Offeror also agrees:

First. To do any extra work, not covered by the attached "Schedule of Items", which may be ordered by the Resident, and to accept as full compensation the amount determined upon a "Force Account" basis as provided in the Standard Specifications, Revision of December 2002, and as addressed in the contract documents.

Second: That the bid band at 5% of the bid amount or the official bank check, cashier's check, certificate of deposit or U. S. Postal Money Order in the amount given in the "Notice to Contractors", payable to the Treasurer of the State of Maine and accompanying this bid, shall be forfeited, as liquidated damages, if in case this bid is accepted, and the undersigned shall fail to abide by the terms and conditions of the offer and fail to furnish satisfactory insurance and Contract bonds under the conditions stipulated in the Specifications within 15 days of notice of intent to award the contract.

Third: To begin the Work on the date specified in the Engineer's "Notice to Commence Work" as stated in Section 107.2 of the Standard Specifications Revision of 2002 and complete the Work within the time limits given in the Special Provisions of this Contract.

Fourth: The Contractor will be bound to the Disadvantaged Business Enterprise (DBE) Requirements contained in the attached Notice (Additional Instructions to Bidders) and submit a completed Contractor's Disadvantaged Business Enterprise Utilization Plan by 4:30pm on the day of bid opening to the Contracts Engineer.

Fifth: That this offer shall remain open for 30 calendar days after the date of opening of bids.

Sixth: The Bidder hereby certifies, to the best of its knowledge and belief that: the Bidder has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of competitive bidding in connection with its bid, and its subsequent contract with the Department.

	etor, for itself, its successors and assigns, hereby greement and thereby binds itself to all covenants, ontract Documents
Date (Witness Sign Here) Witness G. Award. Your offer is hereby accepted. documents referenced herein.	(Sign Here) (Sign Here) (Sign Here) (Sign Here) (Print Name Here) (Name and Title Printed) This award consummates the Contract, and the
	MAINE DEPARTMENT OF TRANSPORTATION
Date	By: David A. Cole, Commissioner
(Witness)	

BOND #	
--------	--

CONTRACT PERFORMANCE BOND

(Surety Company Form)

KNOW ALL MEN BY THESE PRESENTS	S: That
	, as principal,
	,
	rs of the State of and having a
as Surety, are held and firmly bound unto	the Treasurer of the State of Maine in the sum
of	and 00/100 Dollars (\$),
to be paid said Treasurer of the State of payment well and truly to be made, Prince	Maine or his successors in office, for which ipal and Surety bind themselves, their heirs, and assigns, jointly and severally by these
The condition of this obligation is such that	at if the Principal designated as Contractor in
the Contract to construct Project Num	ber in the Municipality of faithfully performs the Contract, then this
obligation shall be null and void; otherwise	
of Maine.	eration or extension of time made by the State
Signed and sealed this	. day of, 20
WITNESSES:	SIGNATURES:
	CONTRACTOR:
Signature	
Print Name Legibly	Print Name Legibly SURETY:
Signature	
Print Name Legibly	Print Name Legibly
SURETY ADDRESS:	NAME OF LOCAL AGENCY: ADDRESS

CONTRACT PAYMENT BOND

(Surety Company Form)

KNOW ALL MEN BY THESE PRES	SENTS: That	
and the	State of	, as principa
and		
a corporation duly organized under th usual place of business in		
as Surety, are held and firmly bound		
and benefit of claimants as		
		nd 00/100 Dollars (\$
for the payment whereof Principal and		
administrators, successors and assigns	-	
The condition of this obligation is su		
the Contract to construct Project		
		aims and demands incurred for a
labor and material, used or required by		_
said Contract, and fully reimburses		_
obligee may incur in making good any		1
be null and void; otherwise it shall ren	nain in full force a	and effect.
A claimant is defined as one havin	g a direct contra	act with the Principal or with
Subcontractor of the Principal for labouse in the performance of the contract.	or, material or bot	_
Signed and sealed this	day of	, 20
WITNESS:	SIGNATU	URES:
	CONTRAC	CTOR:
Signature		
Print Name Legibly		
	SURETY:	
Signature		
Print Name Legibly	Print Name	e Legibly
SURETY ADDRESS:	NAME OF	F LOCAL AGENCY:
		S
TELEPHONE		

SPECIAL PROVISION PARTNERING

The successful bidder will have the opportunity to enter into a cooperative partnership agreement with the State Department of Transportation for the contract. The objective of this agreement is the effective completion of the work on time and to the standard of quality that will be a source of pride to both the State and the Contractor. The partnering agreement will not affect the terms of the contract. It is intended only to establish an environment of cooperation between the partnering agreement is accepted.

- 1. Contractor shall select and provide a third-party facilitator to conduct the team building workshop for the Contractor and Department personnel. Facilitator selection shall require Department concurrence. The cost for the facilitator and his associated expenses will be shared equally by the Department on the next monthly estimate, following receipt of invoice(s) from the Contractor, on an extra work basis.
- 2. Contractor and Department will exchange lists of the key personnel to be participants in the workshop. The list will contain the name and job title of each person, a contact phone number, and the address for job related correspondence.
- 3. The Contractor shall select the location and make all arrangements for space as required by facilitator, and for any meals required. This cost to be shared equally.
- 4. A working arrangement for the partnership will be agreed upon in writing at the workshop. The arrangement will set out the mutually recognized goals and expectation of the parties.
- 5. The Contractor and the Department agree to make an effort to maintain identified key personnel assigned to the work for its duration. A timely notice by each shall be given if changes by either must be made.
- 6. Project issues shall be processed in the manner agreed upon by the parties during the orientation.
- 7. Follow-up workshops may be held periodically throughout the duration of the contract as agreed by the Contractor and the Department.
- 8. The Partnering Agreement is not intended to be a legal document. Failure by either party to follow the process identified will not be grounds for any claim under the contract.
- 9. ARE YOU INTERESTED IN THIS OPPORTUNITY? YES _____ NO ____

SIGNATURE P.E. NUMBER 12.S.ĐŽ SATE DESIGNES
BROJECT MANAGER
PROGRAM

DEPARTMENT OF TRANSPORTATION

APPROVED

STATE OF MAINE

DATE DATE

willedmust

DAWN COFFIN DAWN COFFIN DAWN COFFIN

11269.00




DEPARTMENT OF TRANSPORTATION

STATE OF MAINE


WAITE-TALMADGE-PASSAMAQUODDY TWP.

STP-1126(900)X



PAVEMENT PREVENTATIVE MAINTENANCE PROJECT LENGTH : 7.75 mi STP-1126(900)X WASHINGTON ROUTE 1

TOPSFIELD




TRAFFIC DATA

ASPHALT OVERLAY MILL VARIABLE DEPTH TO SLOPE

1360	205	50.	495
		(рни	
ADT	me	bution P 2.0.	P 2.5
Current (2002) AADT Future (2022) AADT DHV - % of AADT	Design Hour Volume	Directional Distribution (DHV)60 80 kN Equivalent P 2.0505	80 kN Equivalent P 2.5. 495 Design Speed (km/h) 45
nt (20 re (20)	avy Tr	tional N Ecui	N Equi
Curre Futus	Designation No. 1	Direc 80 kl	80 kl Desig

TYPICAL PROPOSED MAINLINE $1\frac{1}{4}$ " of 9.5 mm HMA SURFACE VARIABLE DEPTH MILL & FILL



STATE OF MAINE DEPARTMENT OF TRANSPORTATION

WAITE - TALMADGE PASSAMAQUODDY TWP.
ROUTE 1
NOTESSALE TYPICAL SECTIONS

Waite, Talmadge, Passamaquoddy Township PIN 11269.00 Route 1, PPM

Topo - Left Pole 446	Project Stationi Imperial 18118+00	ng <u>Topo - Right</u>
	18116+68	Pole 445A
Pole 443	18109+92	
	18109+71	Pole 442A
Pole 440	18101+79	
	18100+00	Pole 439A
	18095+25	Passamaquoddy TWP / Waite TL
Pole 437	18093+93	
	18092+45	Pole 436A
	18087+22	Rose Lane
Pole 434	18086+80	
	18080+25	Brace Pole
Pole 431	18078+83	
Pole 428	18069+43	Pole 428S
Pole 425	18060+87	
Pole 422	18052+16	
	18043+92	Woods entrance
Pole 419	18043+40	
Pole 416	18034+74	
Pole 413	18025+29	
BEGIN PROJECT	18020+74	BEGIN PROJECT

Waite, Talmadge, Passamaquoddy Township PIN 11269.00 Route 1, PPM

Pole 485	18228+41	
	18216+79	Pole 481S
	18212+88	Outfitters sign
Pole 482	18212+48	
Pole 479	18211+09	
	18210+30	Gas Pump
Pole 476	18200+48	
Pole 473	18192+77	
	18192+35	Esso Sign
Pole 470	18184+27	
Talmadge Road	18180+73	
Pole 464	18177+72	Pole 464A
	18177+72	Pole 467A
	18162+04	Pole 461A
Pole 461	18159+66	
	18153+12	Pole 458A
Pole 458	18150+48	
Pole 455	18141+97	
Pole 452	18134+27	
	18126+50	Pole 449A
Pole 449	18126+40	

Waite, Talmadge, Passamaquoddy Township PIN 11269.00 Route 1, PPM

	18368+43	Pole 526A
Pole 526	18366+74	
	18359+46	Pole 523A
Pole 523	18358+56	
	18350+38	Pole 520A
Pole 520	18349+74	
Pole 517	18341+24	Pole 517A
	18335+33	Pole 515A
Pole 513	18330+15	
Pole 509	18319+54	Pole 509S
	18311+46	Pole 506D
Pole 505	18299+21	
	18298+42	Talmadge / Waite TL
Pole 500	18285+80	
	18285+38	Pole 500D
	18278+20	Pole 498 1/2S
Pole 497	18271+44	
Pole 494	18261+72	
	18251+16	Woods entrance
Pole 491	18247+10	
Pole 488	18237+44	
	18236+54	Side Road

END PROJECT	18430+26	END PROJECT
Pole 547	18428+89	
	18422+71	Pole 545A
Pole 544	18419+39	
	18413+63	Pole 542A
Pole 541	18410+30	
	18404+55	Pole 539A
Pole 538	18400+75	
	18395+57	Pole 536A
Pole 535	18392+67	
Pole 533	18386+91	
	18386+54	Pole 532A
	18377+57	Pole 529A
Pole 529	18374+98	

Pavement Marking Information

comments	left	right	station
]	18146+83
	L	4	18132+15
		ل	18124+50
	_	<u> </u>	18120+96
	L	┌┆	18114+47
	;	<u> </u>	18112+83
	Ļ	4	18109+08
		_ _	18105+49
	L	_	18100+05
	Ļ	4	18093+87
	<u> </u>	لم	18084+84
	_	<u> </u>	18042+55
		<u> </u>	18033+68
	Ļ	_	18028+72
BEGIN PROJECT			18020+74

Waite, Talmadge, Passamaquoddy Township PIN 11269.00

			Route 1, PPM
	H	18345+15	
		18341+19	
GAP		18340+87	
	Н	18337+07	
	\square	18327+94	
	Ļ	18321+39	
	<u> </u>	18319+44	
	Ļ	18311+73	
	<u>_</u>	18239+65	
	Li	18236+91	
GAP		18236+01	
	Ļ	18232+42	
	<u>, i</u>	18223+13	
		18180+99	
GAP		18180+52	
	Ļ	18177+98	
	<u>i</u>	18155+39	

Waite, Talmadge, Passamaquoddy Township PIN 11269.00 Route 1, PPM

END PROJECT	Ш	18430+26
	Щ	18428+73
	Ļ	18419+86
	<u>, </u>	18402+70
	لبا	18394+62
	<u>;</u>	18393+78
	Ļ	18385+65
	Ļ	18376+04
	ابا	18371+39
	÷	18369+86
	Ļ	18362+52
	<u> </u>	18353+70

Construction Notes

202.202 REMOVING PAVEMENT SURFACE

MAINLINE

Sta. 18020+74 to 18430+26

NOTE: Areas in shoulders to be ground in Undetermined Locations as directed

by Resident.

403.210 HOT MIX ASPHALT, 9.5 mm NOMINAL MAXIMUM SIZE

MAINLINE

Sta. 18020+74 to 18430+26

NOTE: 9.5 mm to be used as shim in Undetermined Locations as directed by Resident.

627.811 TEMPORARY BI-DIRECTION YELLOW DELINEATORS

MAINLINE

Sta. 18020+74 to 18430+26

652.39 WORK ZONE TRAFFIC CONTROL

Lump Sum

CHIEŁ ENGINEEK: HEWATURE HE NUMBER 11-24-03 ATE LILLE SHEET SHEET NUMBER DATE TOPSFIELD DAW KELOEN

BECKNAL

BECKNAL DEPARTMENT OF TRANSPORTATION Rownlothin STATE OF MAINE

PIN 11475.00

DEPARTMENT OF TRANSPORTATION STATE OF MAINE




STA, 9846+80 BEGIN PIN 11475.00 STA, 9847+60 END PIN 11475.00

PIN 11475.00

TOPSFIEI

WASHINGTON ROUTE 6 11475.00

PROJECT LENGTH: 0.02 mi




00.374110

Current (2000) AADT1650 Future (2020) AADT2150	DHV - % of AADT11 Design Hour Volume237	% Heavy Trucks (AADT)15	Directional Distribution (DHV)60	18 kip Equivalent P 2.0212	Design Success (mark)

LOCATION MAP

Ž



Construction Notes

304.104 AGGR SUBBASE COURSE - GRAVEL (PLAN QUANTITY)

STRUT BACKFILL

LOCATION

Sta. 9846+80 to 9847+60

403.207 HOT MIX ASPHALT, 19.0 MM NOMINAL MAXIMUM SIZE

LOCATION WIDTH (ft) DEPTH (in)

Sta 9846+80 to 9847+60 22 6

603.47 60" RCP CLASS IV

LEFT LENGTH (ft) RIGHT LENGTH (ft)

Sta. 9847+20 28 9847+20 28

610.08 PLAIN RIPRAP

LEFT RIGHT

Sta 9847+20 9847+20

NOTE: To be placed on 60" RCP ends

620.58 EROSION CONTROL GEOTEXTILE

LOCATION LENGTH WIDTH (ft)

Sta 9847+20 Under 60" RCP 56' 16' 9847+20 Pipe Ends 7' 16'

652.39 WORK ZONE TRAFFIC CONTROL

Lump Sum

656.75 TEMPORARY SOIL EROSION AND WATER POLLUTION CONTROL PLAN

Lump Sum

GENERAL NOTES

- 1. Where deemed necessary by the Resident, winter sand shall be removed from the edges of shoulders and placed in designated areas or disposed of. Payment will be made under the appropriate contract items.
- 2. All waste material not used on the project shall be disposed of off the project in waste areas approved by the resident.
- 3. Any damage to the slopes caused by the Contractor's equipment, personnel, or operation shall be repaired to the satisfaction of the Resident. All work, equipment and materials required to make repairs shall be at the Contractor's expense.
- 4. Any necessary cleaning of existing pavement prior to paving shall be incidental to the related paving items.
- 5. The following shall be incidental to the 603 item(s):

All pipe and box culvert excavation, including removal and disposal of old box culvert, and cutting and removal of pavement.

All ditching at pipe ends.

Furnishing, Placing, grading, and compacting of any new gravel and/or fill material including Granular Borrow.

Granular Borrow under the pipe shall meet the requirements for underwater backfill.

Flow lines may be changed by 1.5 ft.

Any necessary clearing of brush and small trees at culvert ends.

Furnishing, placing, grading, and compacting of any gravel to be used in Maintenance of Traffic Control including Granular Borrow.

- 6. No separate payment for Superintendent or Foreman will be made for the supervision of equipment being paid under appropriate rental items.
- 7. The Contractor will place side stakes every 100 feet with stationing on them the entire length of the project. Payment to be incidental to the contract
- 8. The grindings from the removal of pavement surface shall be delivered and stockpiled at the Baileyville Maintenance Lot. Payment to be incidental to Item 202.202 Removing Pavement Surface. The materials shall be hauled and stockpiled in one area, pushed up by a loader or similar vehicle.
- 9. All butt joints are considered incidental to item 202.202 Removing Pavement Surface.

- 10. "Undetermined Locations", as stated in the Construction Notes, shall be determined by the Resident.
- 11. Stations referenced in the Construction Notes are approximate.
- 12. All work shall be done in accordance with the Maine Department of Transportation's Best Management Practices for Erosion Control & Sediment Control, January of 2000.
- 13. MDOT will final stripe the project. The Contractor is responsible for transferring the existing striping pattern to the surface course within 24 hours after paving. Payment to be incidental to the contract.
- 14. Instream work shall <u>not</u> be allowed between the dates of October 2, to July 14. Instream work is allowed from July 15, to October 1.
- 15. Grindings will not be considered acceptable cold bituminous mixture for maintaining trenches.

2004

Maintenance Surface Treatment Division 2

Lambert Lake Twp, Codyville Plantation, Topsfield, Vanceboro PIN 11007.30

Project Description	Lane mile	<u>Miles</u>	<u>Tons</u>
Beginning at Route 1 and extending easterly 22 miles To the US-Canada Border	44	22	11,000

SPECIAL PROVISIONS

ASPHALT CONTENT

For bidding purposes, the bidder should use the appropriate percent (%) asphalt content from the table below as the basic asphalt content of the proposed mix. Should the asphalt content require adjusting, the Contractor will be paid an additional sixteen cents (\$0.16/Ton) per Ton for each one-tenth of one percent (0.1%) increase in the asphalt content and/or the State will be allowed a credit of sixteen cents (\$0.16) per Ton for each one-tenth of one percent (0.1%) decrease in the asphalt content with the mix design to be approved by the Division Engineer or the authorized representative.

PIN	<u>AREA</u>	<u>DIVISION</u>	<u>%AC</u>	
11007.30	Lambert Lake Twp., Codyville Plantation, Topsfield, Vanceboro			6.4

GENERAL DECISION ME030011 06/13/03 ME11 General Decision Number ME030011

Superseded General Decision No. ME020011

State: Maine

Construction Type:

HIGHWAY

County(ies):
WASHINGTON

HIGHWAY CONSTRUCTION PROJECTS excluding major bridging (for example: bascule, suspension and spandrel arch bridges; those bridging waters presently navigatin or to be navigable; and thos involving marine construction in any degree); tunnels, building structures in rest area projects and railroad construction

Modification Number Publication Date 0 06/13/2003

COUNTY(ies): WASHINGTON

SUME4027A 10/24/2000

	Rates	Fringes
CARPENTERS	10.00	.76
LABORERS		
Flaggers	6.00	
Unskilled	8.75	
POWER EQUIPMENT OPERATORS		
Backhoes	12.17	
Bulldozers	10.96	
Excavators	10.50	
Loaders	18.23	
Rollers	18.23	
TRUCK DRIVERS		
Dump	9.47	

WELDERS - Receive rate prescribed for craft performing operation to which welding is incidental.

Unlisted classifications needed for work not included within the scope of the classifications listed may be added after award only as provided in the labor standards contract clauses (29 CFR 5.5(a)(1)(ii)).

In the listing above, the "SU" designation means that rates listed under that identifier do not reflect collectively bargained wage and fringe benefit rates. Other designations indicate unions whose rates have been determined to be prevailing.

WAGE DETERMINATION APPEALS PROCESS

1.) Has there been an initial decision in the matter? This can be:

- * an existing published wage determination
- * a survey underlying a wage determination
- * a Wage and Hour Division letter setting forth a position on a wage determination matter
- * a conformance (additional classification and rate) ruling

On survey related matters, initial contact, including requests for summaries of surveys, should be with the Wage and Hour Regional Office for the area in which the survey was conducted because those Regional Offices have responsibility for the Davis-Bacon survey program. If the response from this initial contact is not satisfactory, then the process described in 2.) and 3.) should be followed.

With regard to any other matter not yet ripe for the formal process described here, initial contact should be with the Branch of Construction Wage Determinations. Write to:

Branch of Construction Wage Determinations Wage and Hour Division
U. S. Department of Labor
200 Constitution Avenue, N. W.
Washington, D. C. 20210

2.) If the answer to the question in 1.) is yes, then an interested party (those affected by the action) can request review and reconsideration from the Wage and Hour Administrator (See 29 CFR Part 1.8 and 29 CFR Part 7). Write to:

Wage and Hour Administrator U.S. Department of Labor 200 Constitution Avenue, N. W. Washington, D. C. 20210

The request should be accompanied by a full statement of the interested party's position and by any information (wage payment data, project description, area practice material, etc.) that the requestor considers relevant to the issue.

3.) If the decision of the Administrator is not favorable, an interested party may appeal directly to the Administrative Review Board (formerly the Wage Appeals Board). Write to:

Administrative Review Board U. S. Department of Labor 200 Constitution Avenue, N. W. Washington, D. C. 20210

4.) All decisions by the Administrative Review Board are final. $$\tt END\ OF\ GENERAL\ DECISION\ $}$

State of Maine Department of Labor Bureau of Labor Standards Technical Services Division Augusta, Maine 04333-0045 Telephone (207) 624-6445

Wage Determination - In accordance with 26 MRSA §1301 et. seq., this is a determination by the Bureau of Labor Standards, of the fair minimum wage rate to be paid laborers and workers employed on the below titled project.

Title of Project ----- Maintenance Paving, PIN 11007 30

Location of Project -- Topsfield, Maine in Washington County

2003 Fair Minimum Wage Rates Highway & Earthwork Washington County

	Median	Median			Median	Median	
Occupation Title	<u>Wage</u>	<u>Benefit</u>	<u>Total</u>	Occupation Title	<u>Wage</u>	Benefit	Total
Asphalt Raker	\$10.18	\$3.05	\$13.23	Laborer - Skilled	\$10.05	\$2.30	\$12.35
Backhoe Loader Operator	\$12.25	\$2.53	\$14.78	Loader Op, Front-End	\$16.11	\$3.22	\$19.33
Bulldozer Operator	\$14.35	\$2.47	\$16.82	Mechanic - Maintenance	\$14.78	\$3.42	\$18.20
Cement Mason/Finisher	\$16.00	\$0.00	\$16.00	Paver, Bituminous	\$14.66	\$5.50	\$20.16
Crusher Plant Operator	\$15.41	\$5.50	\$20.91	Pipe/Stm/Sprkler Fitter	\$16.40	\$5.73	\$22.13
Driller, Rock	\$12.72	\$3.05	\$15.77	Pipelayer	\$12.29	\$1.72	\$14.01
Excavator Operator	\$13.50	\$1.44	\$14.94	Roller Operator, Earth	\$16.11	\$4.42	\$20.53
Flagger	\$9.50	\$0.34	\$9.84	Roller Operator, Pavement	\$16.11	\$5.50	\$20.55
Grader/Scraper Operator	\$15.94	\$2.39	\$18.33	Truck Driver, Medium	\$11.00	\$0.17	
Hgway Wrkr/Guardrail Inst	\$10.47	\$1.00	\$11.47	Truck Driver, Heavy	\$10.00		\$11.17
Hot Top Plant Operator	\$16.11	\$6.50	\$22.61	-		\$0.83	\$10.83
Laborers/Helper/Tender	\$9.25			Truck Driver, Tractor Trlr	\$10.63	\$3.15	\$13.78
zasororo, ricipen render	φ9.23	\$1.64	\$10.89	Truck Driver, Mixer, Cemnt	\$10.53	\$5.60	\$16.13

The Laborer classifications include a wide range of work duties. Therefore, if any specific occupation to be employed on this project is not listed in this determination, call the Bureau of Labor Standards at the above number for further clarification.

Welders are classified in the trade to which the welding is incidental.

Apprentices - The minimum wage rate for registered apprentices are those set forth in the standards and policies of the Maine State Apprenticeship and Training Council for approved apprenticeship programs.

Posting of Schedule - Posting of this schedule is required in accordance with 26 MRSA §1301 et. seq., by any contractor holding a State contract for construction valued at \$10,000 or more and any subcontractors to such a contractor.

Appeal - Any person affected by the determination of these rates may appeal to the Commissioner of Labor by filing a written notice with the Commissioner stating the specific grounds of the objection within ten (10) days from the filing of these rates with the Secretary of State.

Determination No:

HI-055-2003

Filing Date:

<u>December 10</u>, 2003

Expiration Date:

12-31-2003

Attest: Jan

A true copy

Director

Bureau of Labor Standards

William A. Peabody

BLS 424HI (R2003) (Highway & Earthwork Washington)

State of Maine Department of Labor Bureau of Labor Standards Technical Services Division Augusta, Maine 04333-0045 Telephone (207) 624-6445

Wage Determination - In accordance with 26 MRSA §1301 et. seq., this is a determination by the Bureau of Labor Standards, of the fair minimum wage rate to be paid laborers and workers employed on the below titled project.

Title of Project ----- Culvert Replacement, PIN 11475.00

Location of Project -- Topsfield, Maine in Washington County

2003 Fair Minimum Wage Rates Highway & Earthwork Washington County

	Median	Median			Median	Median	
Occupation Title	<u>Wage</u>	<u>Benefit</u>	<u>Total</u>	Occupation Title	Wage	Benefit	Total
Asphalt Raker	\$10.18	\$3.05	\$13.23	Laborer - Skilled	\$10.05	\$2.30	\$12.35
Backhoe Loader Operator	\$12.25	\$2.53	\$14.78	Loader Op, Front-End	\$16.11	\$3.22	\$19.33
Bulldozer Operator	\$14.35	\$2.47	\$16.82	Mechanic - Maintenance	\$14.78	\$3.42	\$18.20
Cement Mason/Finisher	\$16.00	\$0.00	\$16.00	Paver, Bituminous	\$14.66	\$5.50	\$20.16
Crusher Plant Operator	\$15.41	\$5.50	\$20.91	Pipe/Stm/Sprkler Fitter	\$16.40	\$5.73	\$22.13
Driller, Rock	\$12.72	\$3.05	\$15.77	Pipelayer	\$12.29	\$1.72	\$14.01
Excavator Operator	\$13.50	\$1.44	\$14.94	Roller Operator, Earth	\$16.11	\$4.42	\$20.53
Flagger	\$9.50	\$0.34	\$9.84	Roller Operator, Pavement	\$16.11	\$5.50	\$21.61
Grader/Scraper Operator	\$15.94	\$2.39	\$18.33	Truck Driver, Medium	\$11.00	\$0.17	\$11.17
Hgway Wrkr/Guardrail Inst	\$10.47	\$1.00	\$11.47	Truck Driver, Heavy	\$10.00	\$0.83	\$10.83
Hot Top Plant Operator	\$16.11	\$6.50	\$22.61	Truck Driver, Tractor Trlr	\$10.63	\$3.15	\$13.78
Laborers/Helper/Tender	\$9.25	\$1.64	\$10.89	Truck Driver, Mixer, Cemnt	\$10.53	\$5.60	\$16.13

The Laborer classifications include a wide range of work duties. Therefore, if any specific occupation to be employed on this project is not listed in this determination, call the Bureau of Labor Standards at the above number for further clarification.

Welders are classified in the trade to which the welding is incidental.

Apprentices - The minimum wage rate for registered apprentices are those set forth in the standards and policies of the Maine State Apprenticeship and Training Council for approved apprenticeship programs.

Posting of Schedule - Posting of this schedule is required in accordance with 26 MRSA §1301 et. seq., by any contractor holding a State contract for construction valued at \$10,000 or more and any subcontractors to such a contractor.

Appeal - Any person affected by the determination of these rates may appeal to the Commissioner of Labor by filing a written notice with the Commissioner stating the specific grounds of the objection within ten (10) days from the filing of these rates with the Secretary of State.

Determination No:

HI-056-2003

Filing Date:

December 11), 2003

Expiration Date:

12-31-2003

Attest: William A. Peabody

A true copy

Director

Bureau of Labor Standards

BLS 424HI (R2003) (Highway & Earthwork Washington)

SPECIAL PROVISION CONSTRUCTION AREA

A Construction Area located in the **Towns of Waite and Talmadge and Township of Passamaquoddy** has been established by the Maine Department of Transportation in accordance with provisions of Title 29, Section 1703, Maine Revised Statutes Annotated.

The section of highway under construction in Washington County, project STP-1126(900)X is located on Route 1, beginning 1.47 miles southerly of the Passamaquoddy/Waite town line and extending northerly 7.76 miles to the Topsfield town line.

The State Department of Transportation or the State's Engineer may issue permits for stated periods of time for moving construction equipment without loads, low-bed trailers with overloads, over-height, over-width or overlength equipment or materials over all State maintained sections described in the "Construction Area" above and in addition may issue permits for stated periods of time for moving overweight vehicles and loads over the section described in (a) above. The right to revoke such a permit at any time is reserved by the State Department of Transportation and the issuance of such permits shall be subject to any Special Provisions or Supplemental Specifications written for this project.

A Temporary Permit for each move may be issued by the State Department of Transportation or the State's Engineer for moving Contractor's construction equipment used on the project which exceeds the legal limits (shovels, bulldozers, etc.) to sources of construction material over highways maintained by the State reasonably within the area of the project.

The Municipal Officers for the **Towns of Waite and Talmadge and Indian TWP – Passamaquoddy Indian Reservation** agreed that a permit will be issued to the Contractor for the purpose of hauling loads in excess of the limits as specified in Title 29, Maine Revised Statues Annotated, on the town ways as described in the "Construction Area" and that single move permits will be issued for moving Contractor's construction equipment used on the project which exceeds the legal limits (shovels, bulldozers, etc.) to sources of construction material over town ways reasonably within the area of the project.


In the event it is necessary to transport gravel, borrow, or other construction material in legally registered vehicles carrying legal loads over town ways, a Contractor's Bond of not more than Nine Thousand (\$9,000.00) per kilometer of traveled length may be required by the town, the exact amount of said bond to be determined prior to use of any town way.

The maximum speed limits for trucks on any town way will be forty (40) km per hour [25 mph], unless a higher legal limit is specifically agreed upon in writing by the Municipal Officers concerned.

STP-1126(900)X

STA. 18020+74 BEGIN PIN 11269.00

STA. 18430+26 END PIN 11269.00



LOCATION MAP



Scale in Miles

SPECIAL PROVISION CONSTRUCTION AREA

A Construction Area located in the **Town of Topsfield** has been established by the Maine Department of Transportation in accordance with provisions of Title 29, Section 1703, Maine Revised Statutes Annotated.

The section of highway under construction in Washington County, PIN 11475.00 is a strut replacement located on Route 6, 0.44 of a mile easterly of Route 1.

The State Department of Transportation or the State's Engineer may issue permits for stated periods of time for moving construction equipment without loads, low-bed trailers with overloads, over-height, over-width or overlength equipment or materials over all State maintained sections described in the "Construction Area" above and in addition may issue permits for stated periods of time for moving overweight vehicles and loads over the section described in (a) above. The right to revoke such a permit at any time is reserved by the State Department of Transportation and the issuance of such permits shall be subject to any Special Provisions or Supplemental Specifications written for this project.


A Temporary Permit for each move may be issued by the State Department of Transportation or the State's Engineer for moving Contractor's construction equipment used on the project which exceeds the legal limits (shovels, bulldozers, etc.) to sources of construction material over highways maintained by the State reasonably within the area of the project.


The Municipal Officers for the **Town of Topsfield** agreed that a permit will be issued to the Contractor for the purpose of hauling loads in excess of the limits as specified in Title 29, Maine Revised Statues Annotated, on the town ways as described in the "Construction Area" and that single move permits will be issued for moving Contractor's construction equipment used on the project which exceeds the legal limits (shovels, bulldozers, etc.) to sources of construction material over town ways reasonably within the area of the project.

In the event it is necessary to transport gravel, borrow, or other construction material in legally registered vehicles carrying legal loads over town ways, a Contractor's Bond of not more than Nine Thousand (\$9,000.00) per kilometer of traveled length may be required by the town, the exact amount of said bond to be determined prior to use of any town way.

The maximum speed limits for trucks on any town way will be forty (40) km per hour [25 mph], unless a higher legal limit is specifically agreed upon in writing by the Municipal Officers concerned.

PIN 11475.00





Scale in Miles

SPECIAL PROVISION CONSTRUCTION AREA

Title 29A, M.R.S.A., Subsection 2383. Overlimit movement permits

- 1. Overlimit movement permits issued by State. The Secretary of State, acting under guidelines and advice of the Commissioner of Transportation, may gant permits to move non-divisible objects having a length, width, height or weight greater than specified in this Title over a way or bridge maintained by the Department of Transportation.
- 2. Permit Fee. The Secretary of State, with the advice of the Commissioner of Transportation, may set the fee for these permits, at not less than \$3, nor more than \$15, based on weight, height, length and width.
- 3. County and municipal permits. A permit may be granted, for a reasonable fee, by county commissioners or municipal officers for travel over a way or bridge maintained by that county or municipality.
- 4. Permits for weight. A vehicle granted a permit for excess weight must first be registered for the maximum gross vehicle weight allowed for that vehicle.
- 5. Special mobile equipment. The Secretary of State may grant a permit, for no more than one year, to move pneumatic-tire equipment under its own power, including Class A and Class B special mobile equipment, over ways and bridges maintained by the Department of Transportation. The fee for that permit is \$15 for each 30-day period.
- 6. Scope of permit. A permit is limited to the particular vehicle or object to be moved and particular ways and bridges.
- 7. Construction permits. A permit for a stated period of time may be issued for loads and equipment employed on public way construction projects, United States Government projects or construction of private ways, when within construction areas established by the Department of Transportation. The Permit:
 - A. Must be procured from the municipal officers for a construction area within that municipality;
 - B. May require the Contractor to be responsible for damage to ways used in the construction areas and ma provide for:
 - (1) Withholding by the agency contraction the work of final payment under contract; or
 - (2) The furnishing of a bond by the Contractor to guarantee suitable repair or payment damages.
 - C. May be granted by the Department of Transportation or by the state engineer in charge of the construction contract; and
 - D. For construction areas, carries no fee and does not come within the scope of this section.
- 8. Gross vehicle weight permits. The following may grant permits to operate a vehicle having a gross vehicle weight exceeding the prescribed limit:

- A. The Secretary of State, with the consent of the Department of Transportation, for state and state aid highways and bridges within city or compact village limits;
- B. Municipal officers, for all other ways and bridges within that city and compact village limits; and
- C. The county commissioners, for county roads and bridges located in unorganized territory.
- 9. Pilot vehicles and state police escorts. Pilot vehicles required by a permit must be equipped with warning lights and signs as required by the Secretary of State with the advice of the Department of Transportation.

Warning lights may only be operated and lettering on the signs may only be visible on a pilot vehicle while it is escorting on a public way a vehicle with a permit.

The Secretary of State shall require a State Police escort for a single vehicle or a combination of vehicles of 125 feet or more in length or 16 feet or more in width. The Secretary of State, with the advice of the Commissioner of Transportation, may require vehicles of lesser dimensions to be escorted by the State Police.

The Bureau of State Police shall establish a fee for State Police escorts.

All fees collected must be used to defray the cost of services provided.

With the advice of the Commissioner of Transportation and the Chief of the State Police, the Secretary of State shall establish rules for the operation for the operation of pilot vehicles.

10. Taxes paid. A permit for a mobile home may not be granted unless the applicant provides reasonable assurance that all property taxes, sewage disposal charges and drain and sewer assessments applicable to the mobile home, including those for the current tax year, have been paid or that the mobile home is exempt from those taxes.

1993, c. 683, § S-2, eff. January 1, 1995.

Historical and Statutory Notes

Derivation:

Laws 1977, c. 73, § 5. Laws 1981, c. 413. R.S. 1954, c. 22 § 98 Laws 1985, c. 225, § 1 Laws 1955, c. 389 Laws 1987. c. 52. Laws 1967, c. 3. Laws 1987, 781, § 3. Laws 1971, c. 593, § 22. Laws 1989, c. 866, § B-13. Laws 1973, c. 213. Laws 1991, c. 388, § 8. Laws 1975, c. 130, § Laws 1993, c. 683, § A-1. Laws 1975, c. 319, § 2 Former 29 M.R.S.A. § 2382.

Cross Reference

Collection by Secretary of State, See 29-A M.R.S.A. § 154.

SPECIAL PROVISION

(Consolidated Special Provisions)

SPECIAL PROVISION SECTION 101 CONTRACT INTERPRETATION

101.2 Definitions - Closeout Documentation

Replace the sentence "A letter stating the amount..... DBE goals." with "DBE Goal Attainment Verification Form"

SPECIAL PROVISION SECTION 102 DELIVERY OF BIDS

(Location and Time)

102.7.1 Location and Time Add the following sentence "As a minimum, the Bidder will submit a Bid Package consisting of the Notice to Contractors, the completed Acknowledgement of Bid Amendments & Submission of Bid Bond Validation Number form, the completed Schedule of Items, 2 copies of the completed Agreement, Offer, & Award form, a Bid Bond or Bid Guarantee, and any other Certifications or Bid Requirements listed in the Bid Book."

SPECIAL PROVISION SECTION 103 AWARD AND CONTRACTING

103.3.1 Notice and Information Gathering

Change the first paragraph to read as follows: "After Bid Opening and as a condition for Award of a Contract, the Department may require an Apparent Successful Bidder to demonstrate to the Department's satisfaction that the Bidder is responsible and qualified to perform the Work."

SPECIAL PROVISION SECTION 105 GENERAL SCOPE OF WORK

105.6.2 Contractor Provided Services

Change the first paragraph by the addition of the following as the second sentence: "The Contractor is also responsible for providing construction centerline, or close reference points, for all Utility Facilities relocations and adjustments as necessary to complete the Work."

SPECIAL PROVISION SECTION 106 QUALITY

106.6 Acceptance Add the following to paragraph 1 of A: "This includes Sections 401 - Hot Mix Asphalt, 402 - Pavement Smoothness, and 502 - Structural Concrete - Method A - Air Content."

Add the following to the beginning of paragraph 3 of A: "For pay factors based on Quality Level Analysis, and"

SPECIAL PROVISION SECTION 107 TIME

<u>107.3.1 General</u> Add the following: "If a Holiday occurs on a Sunday, the following Monday shall be considered a Holiday. Sunday or Holiday work must be approved by the Department, except that the Contractor may work on Martin Luther King Day, President's Day, Patriot's Day, the Friday after Thanksgiving, and Columbus Day without the Department's approval."

SPECIAL PROVISION SECTION 108 PAYMENT

<u>108.4 Payment for Materials Obtained and Stored</u> First paragraph, second sentence, delete the words "...Delivered on or near the Work site at acceptable storage places."

SPECIAL PROVISION SECTION 109 CHANGES

- 109.1.1 Changes Permitted Add the following to the end of the paragraph: "There will be no adjustment to Contract Time due to an increase or decrease in quantities, compared to those estimated, except as addressed through Contract Modification(s)."
- 109.1.2 Substantial Changes to Major Items Add the following to the end of the paragraph: "Contract Time adjustments may be made for substantial changes to Major Items when the change affects the Critical Path, as determined by the Department"
- 109.4.4 Investigation / Adjustment In the third sentence, delete the words "subsections (A) (E)"

- 109.7.2 Basis of Payment Replace with the following: "Equitable Adjustments will be established by mutual Agreement for compensable items listed in Section 109.7.3-Compensable Items, based upon Unit or Lump Sum Prices. If Agreement cannot be reached, the Contractor shall accept payment on a Force Account basis as provided in Section 109.7.5 Force Account Work, as full and complete compensation for all Work relating to the Equitable Adjustment."
- <u>109.7.3 Compensable Items</u> Replace with the following: "The Contractor is entitled to compensation for the following items, with respect to agreed upon Unit or Lump Sum Prices:
 - 1. Labor expenses for non-salaried Workers and salaried foremen.
 - 2. Costs for Materials.
 - 3. A markup on the totals of Items 1 and 2 of this subsection 109.7.3 for home office overhead and profit of the Contractor, its Subcontractors and suppliers, and any lower tier Subcontractors or suppliers, with no mark-ups on mark-ups.
 - 4. Cost for Equipment, based on Blue Book Rates or leased rates, as set forth in Section 109.7.5(C), or the Contractor's Actual Costs.
 - 5. Costs for extended job-site overhead.
 - 6. Time.
 - 7. Subcontractor quoted Work, as set forth below in Section 109.7.5 (F)."

109.7.5 Force Account Work

C. Equipment

Paragraph 2, delete sentence 1 which starts; "Equipment leased...."

Paragraph 6, change sentence 2 from "The Contractor may furnish..." to read "If requested by the Department, the Contractor will produce cost data to assist the Department in the establishment of such rental rate, including all records that are relevant to the Actual Costs including rental Receipts, acquisition costs, financing documents, lease Agreements, and maintenance and operational cost records."

Add the following paragraph; "Equipment leased by the Contractor for Force Account Work and actually used on the Project will be paid for at the actual invoice amount plus 10% markup for administrative costs."

Add the following section;

"<u>F. Subcontractor Quoted Work</u> When accomplishing Force Account Work that utilizes Subcontractor quoted Work, the Contractor will be allowed a maximum markup of 5% for profit and overhead."

SPECIAL PROVISION SECTION 401 HOT MIX ASPHALT PAVEMENT

401.18 Quality Control Method A & B Make the following change to paragraph a. QCP Administrator; in the final sentence, change "...certified as a Plant Technician or Paving Inspector..." to "...certified as a Quality Assurance Technologist..."

<u>401.201 Method A</u> Under <u>a. Lot Size</u>, add the following; 'Each lot will be divided into a minimum of four sublots for mix properties and five sublots for percent TMD."

SPECIAL PROVISION SECTION 402 PAVEMENT SMOOTHNESS

Add the following: "Projects to have their pavement smoothness analyzed in accordance with this Specification will be so noted in Special Provision 403 - Bituminous Box."

<u>"402.02 Lot Size</u> Lot size for smoothness will be 1000 lane-meters [3000 lane-feet]. A sublot will consist of 20 lane-meters [50 lane-feet]. Partial lots will be included in the previous lot if less than one-half the size of a normal lot. If greater than one-half the normal lot size, it will be tested as a separate lot."

SPECIAL PROVISION SECTION 502 STRUCTURAL CONCRETE

502.0502 Quality Assurance Method A - Rejection by Resident Change the first sentence to read: "For an individual sublot with test results failing to meet the criteria in Table #1, or if the calculated pay factor for Air Content is less than 0.80....."

502.0503 Quality Assurance Method B - Rejection by Resident Change the first sentence to read: "For material represented by a verification test with test results failing to meet the criteria in Table #1, the Department will....."

<u>502.0505</u> Resolution of Disputed Acceptance Test Results Combine the second and third sentence to read: "Circumstances may arise, however, where the Department may"

SPECIAL PROVISION SECTION 504 REINFORCING STEEL

504.18 Plates for Fabricated Members Change the second paragraph, first sentence from: "...ASTM A 898/A 898 M..." to "...ASTM A 898/A 898 M or ASTM A 435/A 435 M as applicable and..."

SPECIAL PROVISION SECTION 535 PRECAST, PRESTRESSED CONCRETE SUPERSTRUCTURE

<u>535.02 Materials</u> Change "Steel Strand for Concrete Reinforcement" to "Steel Strand." Add the following to the beginning of the third paragraph; "Concrete shall be Class P conforming to the requirements in this section. 28 day compressive strength shall be as stated on the plans. Coarse aggregate…"

535.26 Lateral Post-Tensioning Replace the first paragraph; "A final tension..." with "Overstressing strands for setting losses cannot be accomplished for chuck to chuck lengths of 7.6 m [25 ft] and less. In such instances, refer to the Plans for all materials and methods. Otherwise, post-tensioning shall be in accordance with PCI standards and shall provide the anchorage force noted in the Plans. The applied jacking force shall be no less than 100% of the design jacking force."

SPECIAL PROVISION SECTION 604 MANHOLES, INLETS, AND CATCH BASINS

<u>604.02 Materials</u> Add the following:

"Tops and Traps 712.07 Corrugated Metal Units 712.08 Catch Basin and Manhole Steps 712.09"

SPECIAL PROVISION SECTION 615 LOAM

615.02 Materials Make the following change:

Organic Content Percent by Volume

Humus "5% - 10%", as determined by Ignition Test

SPECIAL PROVISION SECTION 618 SEEDING

<u>618.01 Description</u> Change the first sentence to read as follows: "This work shall consist of furnishing and applying seed" Also remove ",and cellulose fiber mulch" from 618.01(a).

<u>618.03 Rates of Application</u> In 618.03(a), remove the last sentence and replace with the following: "These rates shall apply to Seeding Method 2, 3, and Crown Vetch."

618.09 Construction Method In 618.09(a) 1, sentence two, replace "100 mm [4 in]" with "25 mm [1 in] (Method 1 areas) and 50 mm [2 in] (Method 2 areas)"

618.15 Temporary Seeding Change the Pay Unit from Unit to Kg [lb].

SPECIAL PROVISION SECTION 620 GEOTEXTILES

620.03 Placement Section (c)

Title: Replace "Non-woven" in title with "Erosion Control".

First Paragraph: Replace first word "Non-woven" with "Woven monofilament". Second Paragraph: Replace second word "Non-woven" with "Erosion Control".

620.07 Shipment, Storage, Protection and Repair of Fabric Section (a)

Replace the third sentence with the following: "Damaged geotextiles, <u>as identified by</u> the Resident, shall be repaired immediately."

620.09 Basis of Payment

Pay Item 620.58: Replace "Non-woven" with "Erosion Control" Pay Item 620.59: Replace "Non-woven" with "Erosion Control"

SPECIAL PROVISION SECTION 626 HIGHWAY SIGNING

626.034 Concrete Foundations Add to the following to the end of the second paragraph: "Pre-cast and cast-in-place foundations shall be warranteed against leaning and corrosion for two years after the project is completed. If the lean is greater than 2 degrees from normal or the foundation is spalling within the first two years, the Contractor shall replace the foundation at no extra cost."

SPECIAL PROVISION SECTION 637 DUST CONTROL

637.06 Basis of Payment Add the following after the second sentence of the third paragraph: "Failure by the Contractor to follow Standard Specification or Special Provision - Section 637 and/or the Contractor's own Soil Erosion and Pollution Control Plan concerning Dust Control and/or visible evidence of excessive dust problems, as determined by the Resident, will result in a reduction in payment, computed by reducing the Lump Sum Total by 5% per occurrence per day. The Department's Resident or any other representative of the Department reserves the right to suspend the work at any time and request a meeting to discuss violations and remedies. The Department shall not be held responsible for any delay in the work due to any suspension under this item. Additional penalties may also be assessed in accordance with Special Provision 652 - Work Zone Traffic Control and Standard Specification 656 - Temporary Soil Erosion and Water Pollution Control."

SPECIAL PROVISION SECTION 656 TEMPORARY SOIL EROSION AND WATER POLLUTION CONTROL

656.5.1 If Pay Item 656.75 Provided Replace the second paragraph with the following: "Failure by the Contractor to follow Standard Specification or Special Provision - Section 656 and/or the Contractor's own Soil Erosion and Pollution Control Plan will result in a reduction in payment, computed by reducing the Lump Sum Total by 5% per occurrence per day. The Department's Resident or any other representative of the Department reserves the right to suspend the work at any time and request a meeting to discuss violations and remedies. The Department shall not be held responsible for any delay in the work due to any suspension under this item."

SPECIAL PROVISION SECTION 709 REINFORCING STEEL AND WELDED STEEL WIRE FABIC

709.03 Steel Strand Change the second paragraph from "...shall be 12mm [½ inch] AASHTO M203M/M203 (ASTM A416/A416M)..." to "...shall be 15.24 mm [0.600 inch] diameter AASHTO M203 (ASTM A416)..."

SPECIAL PROVISION SECTION 712 MISCELLANEOUS HIGHWAY MATERIALS

Add the following:

<u>"712.07 Tops, and Traps</u> These metal units shall conform to the plan dimensions and to the following specification requirements for the designated materials.

Gray iron castings shall conform to the requirements of AASHTO M105, Class 30, unless otherwise designated.

Carbon steel castings shall conform to the requirements of AASHTO M103/M103M. Grade shall be 450-240 [65-35] unless otherwise designated.

Structural steel shall conform to the requirements of AASHTO M183/M183M or ASTM A283/A283M, Grade B or better. Galvanizing, where specified for these units, shall conform to the requirements of AASHTO M111.

712.08 Corrugated Metal Units The units shall conform to plan dimensions and the metal to AASHTO M36/M36M. Bituminous coating, when specified, shall conform to AASHTO M190 Type A.

<u>712.09 Catch Basin and Manhole Steps</u> Steps for catch basins and for manholes shall conform to ASTM C478M [ASTM C478], Section 13 for either of the following material:

- (a) Aluminum steps-ASTM B221M, [ASTM B211] Alloy 6061-T6 or 6005-T5.
- (b) Reinforced plastic steps Steel reinforcing bar with injection molded plastic coating copolymer polypropylene. Polypropylene shall conform to ASTM D 4101.
- <u>712.23 Flashing Lights</u> Flashing Lights shall be power operated or battery operated as specified.
 - (a) Power operated flashing lights shall consist of housing, adapters, lamps, sockets, reflectors, lens, hoods and other necessary equipment designed to give clearly visible signal indications within an angle of at least 45 degrees and from 3 to 90 m [10 to 300 ft] under all light and atmospheric conditions.

Two circuit flasher controllers with a two-circuit filter capable of providing alternate flashing operations at the rate of not less than 50 nor more than 60 flashes per minute shall be provided.

The lamps shall be 650 lumens, 120 volt traffic signal lamps with sockets constructed to properly focus and hold the lamp firmly in position.

The housing shall have a rotatable sun visor not less than 175 mm [7 in] in length designed to shield the lens.

Reflectors shall be of such design that light from a properly focused lamp will reflect the light rays parallel. Reflectors shall have a maximum diameter at the point of contact with the lens of approximately 200 mm [8 in].

The lens shall consist of a round one-piece convex amber material which, when mounted, shall have a visible diameter of approximately 200 mm [8 in]. They shall distribute light and not diffuse it. The distribution of the light shall be asymmetrical in a downward direction. The light distribution of the lens shall not be uniform, but shall consist of a small high intensity portion with narrow distribution for long distance throw and a larger low intensity portion with wide distribution for short distance throw. Lenses shall be marked to indicate the top and bottom of the lens.

(b) Battery operated flashing lights shall be self-illuminated by an electric lamp behind the lens. These lights shall also be externally illuminated by reflex-reflective elements built into the lens to enable it to be seen by reflex-reflection of the light from the headlights of oncoming traffic. The batteries must be entirely enclosed in a case. A locking device must secure the case. The light shall have a flash rate of not less than 50 nor more than 60 flashes per minute from minus 30 °C [minus 20 °F] to plus 65 °C [plus 150 °F]. The light shall have an on time of not less than 10 percent of the flash cycle. The light beam projected upon a surface perpendicular to the axis of the light beam shall produce a lighted rectangular projection whose minimum horizontal dimension shall be 5 degrees each side of the horizontal axis. The effective intensity shall not have an initial value greater than 15.0 candelas or drop below 4.0 candelas during the first 336 hours of continuous flashing. The illuminated lens shall appear to be uniformly bright over its entire illuminated surface when viewed from any point within an angle of 9 degrees each side of the vertical axis and 5 degrees each side of the horizontal axis. The lens shall not be less than 175 mm [7 in] in diameter including a reflex-reflector ring of 13 mm [½ in] minimum width around the periphery. The lens shall be yellow in color and have a minimum relative luminous transmittance of 0.440 with a luminance of 2854° Kelvin. The lens shall be one-piece construction. The lens material shall be plastic and meet the luminous transmission requirements of this specification. The case containing the batteries and circuitry shall be constructed of a material capable of withstanding abuse equal to or greater than 1.21 mm thick steel [No. 18 U.S. Standard Gage Steel]. The housing and the lens frame, if of metal shall be properly cleaned, degreased and pretreated to promote adhesion. It shall be given one or more coats of enamel which, when dry shall completely obscure the metal. The enamel coating shall be of such quality that when the coated case is struck a light blow with a sharp tool, the paint will not chip or crack and if scratched with a knife will not powder. The case shall be so constructed and closed as to exclude moisture that would affect the proper operation of light. The case shall have a weep hole to allow the escape of moisture from condensation. Photoelectric controls, if provided, shall keep the light operating whenever the ambient light falls below 215 lx [20] foot candles]. Each light shall be plainly marked as to the manufacturer's name and model number.

If required by the Resident, certification as to conformance to these specifications shall be furnished based on results of tests made by an independent testing laboratory. All lights are subject to random inspection and testing. All necessary random samples shall be provided to the Resident upon request without cost to the Department. All such samples shall be returned to the Contractor upon completion of the tests.

- 712.32 Copper Tubing Copper tubing and fittings shall conform to the requirements of ASTM B88M Type A [ASTM B88, Type K] or better.
- <u>712.33 Non-metallic Pipe, Flexible</u> Non-metallic pipe and pipe fittings shall be acceptable flexible pipe manufactured from virgin polyethylene polymer suitable for transmitting liquids intended for human or animal consumption.
- <u>712.34 Non-metallic Pipe, Rigid</u> Non-metallic pipe shall be Schedule 40 polyvinylchloride (PVC) that meets the requirement of ASTM D1785. Fittings shall be of the same material.
- <u>712.341 Metallic Pipe</u> Metallic pipe shall be ANSI, Standard B36.10, Schedule 40 steel pipe conforming to the requirements of ASTM A53 Types E or S, Grade B. End plates shall be steel conforming to ASTM A36/A36M.

Both the sleeve and end plates shall be hot dip galvanized. Pipe sleeve splices shall be welded splices with full penetration weld before galvanizing.

- 712.35 Epoxy Resin Epoxy resin for grouting or sealing shall consist of a mineral filled thixotropic, flexible epoxy resin having a pot life of approximately one hour at 10°C [50°F]. The grout shall be an approved product suitable for cementing steel dowels into the preformed holes of curb inlets and adjacent curbing. The sealant shall be an approved product, light gray in color and suitable for coating the surface.
- <u>712.36 Bituminous Curb</u> The asphalt cement for bituminous curb shall be of the grade required for the wearing course, or shall be Viscosity Grade AC-20 meeting the current requirements of Subsection 702.01 Asphalt Cement. The aggregate shall conform to the requirements of Subsection 703.07. The coarse aggregate portion retained on the 2.36 mm [No. 8] sieve may be either crushed rock or crushed gravel.

The mineral constituents of the bituminous mixture shall be sized and graded and combined in a composite blend that will produce a stable durable curbing with an acceptable texture. Bituminous material for curb shall meet the requirements of Section 403 - Hot Bituminous Pavement.

<u>712.37 Precast Concrete Slab</u> Portland cement concrete for precast slabs shall meet the requirements of Section 502 - Structural Concrete, Class A.

The slabs shall be precast to the dimension shown on the plans and cross section and in accordance with the Standard Detail plans for Concrete Sidewalk Slab. The surface shall be finished with a float finish in accordance with Subsection 502.14(c). Lift devices of sufficient strength to hold the slab while suspended from cables shall be cast into the top or back of the slab.

<u>712.38 Stone Slab</u> Stone slabs shall be of granite from an acceptable source, hard, durable, predominantly gray in color, free from seams which impair the structural integrity and be of smooth splitting character. Natural color variations characteristic of the deposit will be permitted. Exposed surfaces shall be free from drill holes or indications of drill holes. The granite slabs in any one section of backslope must be all the same finish.

The granite slabs shall be scabble dressed or sawed to an approximately true plane having no projections or depressions over 13 mm [½ in] under a 600 mm [2 ft] straightedge or over 25 mm [1 in] under a 1200 mm [4 ft] straightedge. The arris at the intersection of the top surface and exposed front face shall be pitched so that the arris line is uniform throughout the length of the installed slabs. The sides shall be square to the exposed face unless the slabs are to be set on a radius or other special condition which requires that the joints be cut to fit, but in any case shall be so finished that when the stones are placed side by side no space more than 20 mm [3/4 in] shall show in the joint for the full exposed height.

Liftpin holes in all sides will be allowed except on the exposed face.

SPECIAL PROVISION SECTION 717 ROADSIDE IMPROVEMENT MATERIAL

717.05 Mulch Binder. Change the third sentence to read as follows:

"Paper fiber mulch may be used as a binder at the rate of 2.3 kg/unit [5 lb/unit]."

TOWN: Passamaquoddy (Ind. Twp.) – Talmadge

Project: **PIN# 11269.00**Date: **November 24, 2003**

SPECIAL PROVISIONS SECTION 104 Utilities

MEETING

A Preconstruction Utility Conference, as defined in Subsection 104.4.6 of the Standard Specifications **is not** required.

GENERAL INFORMATION

These Special Provisions outline the arrangements that have been made by the Department for utility and/or railroad work to be undertaken in conjunction with this project. The following list identifies all known utilities or railroads having facilities presently located within the limits of this project or intending to install facilities during project construction

Overview:

Utility/Railroad	Aerial	Underground	Railroad
Eastern Maine Electric Coop., Inc.	X		
Verizon	X		

Temporary utility adjustments are **not** anticipated.

No utility adjustments are anticipated as part of this project.

If necessary, all adjustments are to be made by the respective utility/railroad unless otherwise specified herein.

Utility Contacts:

Eastern Maine Electric Coop., Inc. Andrew Tickle (207)454-7555 Ext. 156

Verizon Mike Samiya (207)990-5228

BDM Page 1 of 1 Utility Spec (Ver. 12.00)

Town: **Topsfield**

Project: **PIN# 11475.00**Date: **November 24, 2003**

SPECIAL PROVISIONS SECTION 104 Utilities

MEETING

A Preconstruction Utility Conference, as defined in Subsection 104.4.6 of the Standard Specifications **is not** required.

GENERAL INFORMATION

These Special Provisions outline the arrangements that have been made by the Department for utility and/or railroad work to be undertaken in conjunction with this project. The following list identifies all known utilities or railroads having facilities presently located within the limits of this project or intending to install facilities during project construction

Overview:

Utility/Railroad	Aerial	Underground	Railroad
Eastern Maine Electric Coop., Inc.	X		
Verizon	X		

Temporary utility adjustments are **not** anticipated.

No utility adjustments are anticipated as part of this project.

If necessary, all adjustments are to be made by the respective utility/railroad unless otherwise specified herein.

Utility Contacts:

Eastern Maine Electric Coop., Inc. Andrew Tickle (207)454-7555 Ext. 156

Verizon Mike Samiya (207)990-5228

BDM Page 1 of 1 Utility Spec (Ver. 12.00)

Town: Topsfield PIN #: 11475. 00 Date: 12/10/2003

SPECIAL PROVISION SECTION 105

General Scope of Work (Environmental Requirements)

Instream Work shall <u>not</u> be allowed between the dates of 10/2 and 7/14. (Instream work is allowed from 7/15 to 10/1.)

Stream Name(s) with Station #s: Lindsey Brook

Special Conditions: Instream work shall be conducted during low flows.

Instream work consists of any activity conducted below the normal high water mark.

During the instream work window restriction, all activities are <u>prohibited</u> (including placement and removal of cofferdams) below the normal high water mark and during high flow conditions, except for the following:

• Work within a sealed and dewatered cofferdam. Maintenance pumping within a sealed cofferdam is also allowed.

No construction activity, whether temporary or permanent, is allowed that completely blocks a river, stream, or brook without providing downstream flow.

The contractor shall abide by all permits and conditions.

SPECIAL PROVISION <u>SECTION 107</u> SCHEDULING OF WORK

Replace Section 107.4.2 with the following:

<u>"107.4.2 Schedule of Work Required</u> Within 21 Days of Contract Execution and before beginning any on-site activities, the Contractor shall provide the Department with its Schedule of Work. The Contractor shall plan the Work, including the activity of Subcontractors, vendors, and suppliers, such that all Work will be performed in Substantial Conformity with its Schedule of Work. The Schedule must include sufficient time for the Department to perform its functions as indicated in this Contract, including QA inspection and testing, approval of the Contractor's TCP, SEWPCP and QCP, and review of Working Drawings.

At a minimum, the Schedule of Work shall include a bar chart which shows the major Work activities, milestones, durations, and a timeline. Milestones to be included in the schedule include: (A) start of Work, (B) beginning and ending of planned Work suspensions, (C) Completion of Physical Work, and (D) Completion. If the Contractor Plans to Complete the Work before the specified Completion date, the Schedule shall so indicate.

Any restrictions that affect the Schedule of Work such as paving restrictions or In-Stream Work windows must be charted with the related activities to demonstrate that the Schedule of Work complies with the Contract.

The Department will review the Schedule of Work and provide comments to the Contractor within 20 days of receipt of the schedule. The Contractor will make the requested changes to the schedule and issue the finalized version to the Department."

SPECIAL PROVISION SECTION 107 Time (Contract Time)

- 1. The Contractor will be allowed to commence work at any time after July 19, 2004 providing that all applicable plans required under this contract have been submitted and approved.
- 2. For every weekday not worked once operation commences, (excluding inclement weather days) the Contractor will be charged supplemental Liquidated Damages at the rate of \$950.00 per day.
- 3. All work shall be completed by September 04, 2004.

SPECIAL PROVISIONS DIVISION 400 PAVEMENTS

<u>Description.</u> This work shall consist of supplying the aggregate and bitumen, trucking, and producing Maintenance Resurfacing HMA (Hot Mix Asphalt) for use as directed by the Maintenance Division. The mixture shall be placed as directed by the <u>Department</u>.

MATERIALS

HMA MIX TYPE. The Hot Mix Asphalt Type shall be 9.5 mm Fine or 9.5 mm Fine w/RAP.

<u>Bituminous Material.</u> The bituminous material shall meet the requirement of the State of Maine, Department of Transportation, Standard Highway Specifications, Revision of December 2002. The asphalt shall meet the grading requirements of PG 64-28 or PG 64-22.

<u>Aggregate</u>. Aggregate shall consist of clean, tough durable fragments free from an excess of flat, elongated, soft or disintegrated particles. It shall be processed from a gravel or stone source in such a manner that a uniformly graded stockpile of sufficient quantity for at least on day's normal production will be available at all times. Production of the mix will come from prepared stockpiles.

Materials. Materials shall meet the following Consensus Quality requirements:

The Composite Blend shall have a Micro-Deval value of 18.0 or less as determined by AASHTO TP-58-99. In the event of a failure, the Washington Degradation test of 1967 shall be run before rejection of the material. Material with a value of 30 or more may be accepted. The fine aggregate shall not exceed absorption of 3% by weight as determined by AASHTO T84.

The Sand Equivalent value shall be a minimum of 45 as determined by AASHTO T304. The uncompacted Void Content of Fine Aggregate shall be a minimum of 40 as d determined by AASHTO T304.

Composition of Mixtures The Contractor shall compose the Hot Mix Asphalt Pavement with aggregate, Performance Graded Asphalt Binder (PGAB), and mineral filler if required. The Contractor shall size, uniformly grade, and combine the aggregate fractions in proportions that provide a mixture meeting the grading requirements of the Job Mix Formula (JMF). The Contractor may use a maximum of 15% reclaimed asphalt pavement (RAP).

The Contractor shall submit for Department approval a JMF to the Central Laboratory in Bangor. The JMF shall establish a single percentage of aggregate passing each required sieve size within the limits shown in Table A. The JMF shall state the source, gradation, and percentage to be use of each portion of the aggregate and mineral filler if required. It shall also

state the proposed PGAB content, the name and location of the refiner, the supplier, the source of PGAB submitted for approval, the type of PGAB modification if applicable, and the location of the terminal if applicable. All mixes utilized in this contract work shall be from a single Hot Mix Asphalt source to minimize the testing requirements, unless otherwise authorized by the Department.

The mix design air void target is 4.0 % at **50 gyrations** for all HMA mixes placed under this contract

CONSTRUCTION REQUIREMENTS

<u>Weather Limitations.</u> Weather conditions shall be satisfactory for the safety of the operation and shall be carried on only when the atmospheric temperature is above 50° F and pavement temperature is above 40° F. Placement of HMA will not be allowed on wet surfaces.

<u>Gradation Testing.</u> Control of the mix <u>production</u> will be maintained by requiring that the running average of three consecutive **washed gradation tests** fall within the required gradation limits <u>outlined</u> in Table A.

Property - Gradation	Specification Limits
Square Mesh Sieve	Percent Passing
1/2"	100
# 4	70 - 100
# 16	26 - 75
# 50	10 - 30
# 200	2 - 8

TABLE A

The Contractor shall be required to provide a report of a minimum of three passing **washed gradations** from each plant site. The location for sampling will be either from the incline belt on a drum mixer plant, a dry batch through the pugmill or a combined hot bin sample on a batch plant. In lieu of the dry samples the gradation achieved from an extracted mix sample would be acceptable.

The first gradation will be taken prior to production, the second taken during the first day of production. The final test will be taken when 50% of contract has been completed. A copy of the test result will be made available to the Department, or authorized representative, before the next working day after the test is require. At the same time, a copy will be sent by the Contractor to the Maintenance and Operations Bureau, 16 State House Station, Augusta, Maine 04333-0016 to the attention of the Hot Maintenance Mulch Manager. Blank forms will be available through the Division Engineer or the authorized representative upon request. The Division Engineer or authorized representative may require that a sample be procured and tested by State personnel prior to the start of operations.

These tests in no way relieve the Contractor from control testing to maintain the quality and consistency of the product. Nothing in this section prevents the Department of Transportation's personnel from obtaining additional samples of products to assure the acceptability of the product.

401.203 Quality Control - Method C

The Department will obtain samples of Hot Mix Asphalt Pavement in conformance with AASHTO T168 Sampling Bituminous Paving Mixtures, and the MDOT/ ACM Sampling Policy. The Department will take the samples randomly within each sublot.

For hot mix asphalt items designated as Method C, the total quantity of mix represented in the Contract shall constitute a Lot. Each Lot shall be divided into a minimum of **four (4)** sublots.

The maximum sublot size shall be **2500 ton**. Each sublot sample will be taken from the paver hopper, or the truck body, per pay item. The samples will then be transported by the Contractor to the designated MDOT Laboratory as directed by MDOT. All samples will be placed in approved transport containers to be provided by the Department, unless otherwise directed by the Department. The mix will be tested for gradation and PGAB content. Disputes will not be allowed. If the mix is within the tolerances listed in Table 7 - Method C Acceptance Limits, the Department will pay the contract unit price. Target values shall be as specified in the JMF.

TABLE 7: METHOD C ACCEPTANCE LIMITS

Property	USL and LSL
	Method C
Percent Passing No. 4 and larger	Target ± 7
sieves	
Percent Passing No. 8 to No. 16	Target ± 5
sieves	
Percent Passing No. 30	Target ± 4
Percent Passing No. 50 to No. 200	Target ± 3
sieve	
PGAB Content	Target ± 0.5

If the test results for each sublot outside the Table 7 property limits the following deductions in Table 7b shall apply to the HMA quantity represented by the test. A second consecutive test outside acceptance criteria shall result in cessation of mix production.

TABLE 7b

PGAB Content	-5%
2.36 mm sieve	-2%
0.30 mm sieve	-1%
0.075 mm sieve	-2%

The Department will use Table 7b for calculating pay factors for gradation and PGAB content.

Onsite certified QC personnel shall not be required.

<u>Hot Mix Asphalt Plant Requirements.</u> All Bituminous mixing plants shall conform to the Standard Specifications, Revision of December 2002.

<u>Mixing Operations.</u> The processing of the aggregate, handling of bitumen, drying of aggregate, and mixing shall conform with acceptable practices of the paving industry. The Contractor's plant shall supply a minimum of 90 ton/hour at the paver.

The Contractor shall provide silicon additive when requested by the Division Engineer or authorized representative.

The Contractor shall provide an approved release agent, and application equipment, to safely apply a sufficient coating of release agent to prevent the HMA mixture from adhering to the truck beds

<u>Traffic Control.</u> The State will provide all necessary traffic control and sweeping operations.

<u>Placing Operations.</u> The Contractor shall be responsible for the actual placing and rolling operations. Placing operations shall conform to acceptable paving practices. Mixture produced under this contract shall be placed on the roadway with an approved self-propelled bituminous finishing machine designed for highway paving. Immediately after the material is spread, a sufficient number of 7-10 ton, 2-axle steel wheel and/or rubber tired rollers, as determined by the Division Engineer or authorized representative, shall be utilized to properly compact it.

The Contractor shall provide sufficient personnel at the paver to assure placement of the pavement in an orderly, safe, and efficient manner, and so as to assure a quality mat and proper overall yield.

Every effort shall be made to close exposed longitudinal joints within two (2) working days, and on weekends and holidays.

In the event the Contractor's placing equipment breaks down, the State may place the mixture in transit if State equipment is readily available and if it is a type which can perform the work satisfactorily. This cost of placing will be borne by the Contractor.

Onsite certified QC personnel shall not be required.

<u>Dust Control.</u> The Contractor is responsible for dust control on the access roads for the bituminous plant as described in Section 637 of the Standard Highway Specifications, Revision of December 2002. This work shall be incidental to the contract.

Method of Measurement. Maintenance Surface Treatment (HMA) will be measured by the ton, at the contract price, according to delivery slips. Material not placed and compacted satisfactorily due to Contractor's equipment failure will not be measured for payment. The delivery slips shall conform to the requirements of the Standard Highway Specifications, Revision of December 2002. Cover slips will be required to be delivered on the next working day after each paying day. Listed will be the Item number, date and quantity.

<u>Basis of Payment.</u> Maintenance Surface Treatment (HMA) will be paid for at the contract unit price per ton. Such payment shall be full compensation for obtaining and furnishing all aggregate and bituminous material including tack; for processing, heating, mixing, weighing, trucking, placing, and rolling; for furnishing all labor, equipment, tools and all incidentals necessary to complete the work.

When work is to be accepted under Method C provisions, the Department will make a pay adjustment for quality below the minimum acceptable level, as specified on Table 7b.

Payment will be made under:

Pay Item		Pay Unit
461.210	Maintenance Surface Treatment (HMA), 9.5 mm	Ton

Waite-Talmadge-Passamaquoddy PPM-Mill and Overlay STP-1126(900)X December 10, 2003

SPECIAL PROVISION SECTION 403 HOT MIX ASPHALT OVERLAY

Desc. of Course	Grad. Design	Item Number	Bit Cont. % of Mix	Total Thick	No. Of Layers	Comp. Notes
			and Overlay Anline Traveled			
Wearing	9.5mm	403.210	N/A	11/4"	1	4,7

COMPLEMENTARY NOTES

- 2. The density requirements are waived.
- 3. The design traffic level for mix placed shall be <0.3 million ESALS.
- 4. The design traffic level for mix placed shall be 0.3 to <3 million ESALS.
- 7. Section 106.6 Acceptance, (1) Method A.
- 9. Section 106.6 Acceptance, (2) Method C.

Tack Coat

A tack coat of emulsified asphalt, RS-1 or HFMS-1, Item #409.15 shall be applied to any existing pavement at a rate of approximately 0.025 G/SY, and on milled pavement approximately 0.05 G/SY, prior to placing a new course. A fog coat of emulsified asphalt shall be applied between shim / intermediate course and the surface course, at a rate not to exceed 0.08 L/m².

Tack used between layers of pavement will be paid for at the contract unit price for Item 409.15 Bituminous Tack Coat.

Topsfield Strut 11475.00 December 10, 2003

SPECIAL PROVISION SECTION 403 HOT MIX ASPHALT OVERLAY

Desc. of Course	Grad. Design	Item Number	Bit Cont. % of Mix	Total Thick	No. Of Layers	Comp. Notes			
<u>Strut</u>									
Mainline Traveled Way									
Wearing	19.0mm	403.207	N/A	6 "	2/more	4,9			

COMPLEMENTARY NOTES

- 2. The density requirements are waived.
- 3. The design traffic level for mix placed shall be <0.3 million ESALS.
- 4. The design traffic level for mix placed shall be 0.3 to <3 million ESALS.
- 9. Section 106.6 Acceptance, (2) Method C.

Tack Coat

A tack coat of emulsified asphalt, RS-1 or HFMS-1, Item #409.15 shall be applied to any existing pavement at a rate of approximately 0.025 G/SY, and on milled pavement approximately 0.05 G/SY, prior to placing a new course. A fog coat of emulsified asphalt shall be applied between shim / intermediate course and the surface course, at a rate not to exceed 0.08 L/m².

Tack used between layers of pavement will be paid for at the contract unit price for Item 409.15 Bituminous Tack Coat.

Special Provision
Section 652
Maintenance of Traffic(Traffic Control)
May 12, 2003
Supercedes December 10, 2001

SPECIAL PROVISION <u>SECTION 652</u> MAINTENANCE OF TRAFFIC

(Traffic Control)

652.7 Method of Measurement. This entire Subsection is revised to read:

Traffic Control Supervisor, furnishing, installation, and maintenance of all traffic control devices **including flaggers** will be measured as one **lump sum** for all work authorized and performed.

652.8 Basis of Payment. This entire Subsection is revised to read:

Traffic Control will be paid for at the contract **lump sum** price. Payment will be full compensation for the Traffic Control Supervisor, flaggers, approach signs, work area signs, drums, cones, panel markers, barricades, arrow boards etc. and maintenance thereof including the setting up and taking down of lane closures as many times as necessary shall be considered part of the lump sum price.

Maintenance of signs includes: replacing devices damaged, lost, or stolen, and cleaning and moving as many times as necessary throughout the life of the contract, regardless whether the work areas or projects are geographically separated or not separated.

The Lump Sum will be payable in installments as follows: 5% of the Lump Sum once the approach signing is complete and approved, with the 95% balance to be paid as the work progresses at a rate proportional to the percentage completion of the Contract.

Failure by the contractor to follow the Contracts 652 Special Provisions and/or The Manual on Uniform Traffic Control Devices (MUTCD) and/or The Contractors own Traffic Control Plan will result in a reduction in payment, computed by reducing The Lump Sum Total by 5% per occurrence. The Departments Resident Engineer or any other representative of The Department reserves the right to suspend the work at any time and request a meeting to discuss violations and remedies. The Department shall not be held responsible for any delay in the work due to any suspension under this item.

All other requirements under the Standard Specifications Section 652 will be a part of the lump sum item.

There will be no extra payment for this pay item after the expiration of contract time.

Payment will be made under:

Pay Item 652.39 Work Zone Traffic Control Pay Unit Lump Sum

SPECIAL PROVISION <u>SECTION 652</u> MAINTENANCE OF TRAFFIC

<u>Approaches</u> Approach signing shall include the following signs as a minimum. Field conditions may warrant the use of additional signs as determined by the Resident.

Road Work Next x Miles Road Work 500 Feet End Road Work

Work Area At each work site, signs and channelizing devices shall be used as directed by the Resident. Signs include:

Road Work xxxx¹ One Lane Road Ahead Flagger Sign

Other typical signs include:

Be Prepared to Stop Low Shoulder Bump Pavement Ends

The above lists of Approach signs and Work Area signs are representative of the contract requirements. Other sign legends may be required.


The Contractor shall conduct their operations in such a manner that the roadway will not be restricted to one lane for more than 800 m [2,500 ft] at each work area. Where more than one work area restricts traffic to one lane operation, these work areas shall be separated by at least 1.6 km [1 mile] of two way operation.


<u>Temporary Centerline</u> A temporary centerline shall be placed each day on all new pavement to be used by traffic. The temporary centerline, when specified of reflectorized traffic paint, shall conform to the standard marking patterns used for permanent markings.

Failure to apply a temporary centerline daily will result in suspension of paving until temporary markers are applied to all previously placed pavement.

¹ "Road Work Ahead" to be used in mobile operations and "Road Work xx ft" to be used in stationary operations as directed by the Resident.

TYPICAL -- PROJECT APPROACH SIGNING --TWO WAY TRAFFIC





TYPICAL APPLICATION: TWO - WAY, TWO LANE ROADWAY, **CLOSING ONE LANE USING FLAGGERS**

		L
I TE OF IAPER	I APER LENGIA (L)	For spee
Merging Taper	at least L	$L = \frac{WS^2}{80}$
Shifting Taper	at least 0.5L	For spee
Shoulder Taper	at least 0.33L	L = WS
One-Lane, Two-Way Traffic Taper 100 ft (30 m) maximum	100 ft (30 m) maximum	* Form
Downstream Taper	100 ft (30 m) per lane	A minim

• •
Ø
2
<
\underline{u}
\equiv
.0
—
S
as
••
(D)
æ
$\boldsymbol{\omega}$
_
_
ō
₽
40
92
$\boldsymbol{\sigma}$
=
=
⊱
Ō
ıτ
ш
*

ed limits of 40 mph (60 km/h) or less:

$$- = \frac{WS^2}{60}$$
 (L = $\frac{WS^2}{155}$)

ed limits of 45 mph (70 km/h) or greater:

$$\frac{\tilde{SM}}{\tilde{SM}} = 1$$
 $SM = 1$

WS
$$(L = \frac{WS}{1.6})$$

Formulas for L are as follows:

num of 5 channelization devices shall be used in the taper.

CHANNELIZATION DEVICE SPACING

when used for taper channelization, and a distance in feet of 2.0 times the speed limit in mph when used for The spacing of channelization devices shall not exceed a distance equal to 1.0 times the speed limit in mph tangent channelization.

SIGN SPACING TABLE	ING TABLE		
Dood Tyno	Distance	Distance Between Signs**	gns**
Noad Type	∢	B	ပ
Urban 30 mph (50 km/h) or less	100 (30)	100 (30)	100 (30)
Urban 35 mph (55 km/h) and greater	350 (100)	350 (100)	350 (100)
Rural	500 (150)	500 (150)	500 (150)
Expressway / Urban Parkway	2,640 (800) 1,500 (450)	1,500 (450)	1000 (300)

GENERAL NOTES;

1. Final placement of signs and field conditions as approved by devices may be changed to fit the Resident.

**Distances are shown in feet (meters).

SUGGESTED BUFFER ZONE LENGTHS

Length (feet	325	360	425	495
Length (feet) Speed (mph)	40	45	09	22
Length (feet)	115	155	200	250
Speed (mph)	20	25	30	35

(mph)	Length (feet)	Length (feet) Speed (mph)	Length (feet)
20	115	40	325
25	155	45	360
30	200	50	425
35	250	55	495

SPECIAL PROVISION SECTION 656

Temporary Soil Erosion and Water Pollution Control

The following is added to Section 656 regarding Project Specific Information and Requirements. All references to the Maine Department of Transportation Best Management Practices for Erosion and Sediment Control (a.k.a. Best Management Practices manual or BMP Manual) are a reference to the latest revision of said manual. The "Table of Contents" of the latest version is dated "1/19/00" (available at http://www.state.me.us/mdot/mainhtml/bmp/bmpjan2000.pdf.)

Procedures specified shall be according to the BMP Manual unless stated otherwise.

Delete the last sentence of Section 656.4.4, which reads, "After Final Acceptance of the project, the Contractor must submit the log to the Department which will become the property of the Department."

Any and all references to "bark mulch" or "composted bark mix" shall be a reference to "Erosion Control Mix" in accordance with *Standard Specification*, *Section 619 - Mulch*.

Project Specific Information and Requirements

The following information and requirements apply specifically to this Project. The temporary soil erosion and water pollution control measures associated with this work shall be addressed in the SEWPCP.

- 1) This project is in the St. Croix River watershed and is considered **SENSITIVE** in accordance with the BMP Manual. The Contractor's SEWPCP shall comply with Section II.B., <u>Guidelines</u> for Sensitive Water bodies in the BMP Manual.
- 2) Newly disturbed earth shall be mulched by the end of each workday. Mulch shall be maintained on a daily basis.
- 3) The SEWPCP shall describe the location and method of temporary erosion and sediment control for existing and proposed catch basins, outlet areas and culvert inlets and outlets.
- 4) Dust control items other than those under *Standard Specification*, *Section 637* <u>Dust Control</u>, if applicable, shall be included in the plan.
- 5) Permanent slope stabilization measures shall be applied within one week of the last soil disturbance.

SPECIAL PROVISION SECTION 656

Temporary Soil Erosion and Water Pollution Control

- 6) Permanent seeding shall be done in accordance with *Standard Specification*, *Section 618* <u>Seeding</u> unless the Contract states otherwise.
- 7) Culvert inlet and outlet protection shall be installed within 48 hours of culvert installation, or prior to a storm event, whichever is sooner.
- 8) All disturbed ditches shall be stabilized by the end of each workday. Stabilization shall be maintained on a daily basis.
- 9) Erosion control blanket shall be installed in the bottoms of all ditches except where a stone lining is planned. Seed shall be applied prior to the placement of the blanket.
- 10) If check dams are used, they shall be constructed of stone in accordance with BMP Manual, Section 9.
- 11) If water is flowing within the drainage system, the water shall be diverted to a stable area or conduit and work shall be conducted in the dry. The Contractor's plan shall address when and where the diversions will be necessary.
- 12) Demolition debris (including debris from wearing surface removal, saw cut slurry, dust, etc.) shall be contained and shall not be allowed to discharge to any resource. All demolition debris shall be disposed of in accordance with *Standard Specifications*, *Section 202.03*, *Removing Existing Superstructure*, *Structural Concrete*, *Railings*, *Curbs*, *Sidewalks and Bridges*. Containment and disposal of demolition debris shall be addressed in the Contractor's SEWPCP.
- **13) CLEARING LIMIT LINES SHALL BE MINIMIZED.** Clearing shall be minimized as shown on the design plans.
- 14) Class A and AA Waters General in-stream work other than slip/ invert lining for class A and AA waters

Stream flow shall be maintained at all times.

SPECIAL PROVISION SECTION 656

Temporary Soil Erosion and Water Pollution Control

Grout from the post-tensioning socket sealing operation and fresh concrete shall not be allowed to contact the stream. Clean out of concrete delivery trucks and the washing of tools shall be addressed in the SEWPCP.

The SEWPCP shall describe the containment method for removal of the existing abutments, including installation of cofferdams and dewatering procedures.

A cofferdam sedimentation basin is required if cofferdams are used. The basin shall be located in an upland area where the water can settle and seep into the ground or be released slowly to the resource in a manner that will not cause erosion. The location of such a cofferdam sedimentation basin shall be addressed in the SEWPCP.

OR

If a cofferdam sedimentation basin is used, it shall be located in an upland area where the water can settle and sink into the ground or be released slowly to the resource in a manner that will not cause erosion. The location of such a cofferdam sedimentation basin shall be addressed in the SEWPCP.

Prior to release to a natural resource, any impounded water that has been in contact with concrete placed during construction must have a pH between 6.0 and 8.5, must be within one pH unit of the background pH level of the resource and shall have a turbidity no greater than the receiving resource. This requirement is applicable to concrete that is placed or spilled (including leakage from forms) as well as indirect contact via tools or equipment. Water not meeting release criteria shall be addressed in the SEWPCP. Discharging impounded water to the stream must take place in a manner that does not cause erosion or disturb the stream bottom. The rate of discharge must be less than 20% of the flow rate of the stream.

The Contractor shall be responsible for monitoring pH with a calibrated meter accurate to 0.1 units. A record of pH measurements shall be kept in the Environmental Coordinator's log (Section 656.4.4.)

l'ermite	3 & 6	YUGG	urau	Kes.	30U	ree	3 💯	D U	₹
PIN #: 11475.00									
Location: Topsfield	DI .		D . 1	л · 🖂	D 1	ENWO	11	10/10/	0.2
Permit Member: Laurie Rowe	Photogi	raphs \square	Database	Projex ⊠	Раска	ge to ENV Co	oordinator:	12/10/0	03
	RAL RESOUR	CES							
MHPC Historic Resor		020	N/A □	Applicable	X	Approved	× 1	MOA	
MHPC Archeological	Resources		N/A □	Applicable		Approved		MOA	
Tribal Consultation			N/A □	Applicable		Approved			
☒ 4(f) and 6(f)									
Section 4(f)		N/A ⊠ N/A ⊠	Applical		Approved				
LAWCON 6(f)		N/A 🖾	Applical	oie⊔ A	Approved	1 ⊔			
区 FEMA		N/A×	Applicab	1eП A	Approved	· 🗆			
E FEMA		IV/AL	Аррисао		ърргочес				
☒ Maine Department of Env	vironmental Pro	tection (N	MDEP) Sit	e Location o	of Devel	opment			
	pplicable 🗆	Approve				•			
区 Local Zoning, Title 30-A	Section 4352-6								
Is the project something of			oridge syste	em, such as a	a mainte	nance lot. b	uilding/pa	rking f	acility? Yes
\square No \boxtimes . If no, the pro		way and c	mage syste	oni, sacii as t	a mame	nunce iou, o	anam _g pe	iiiiiig i	acinty. 10.
If yes, continue. Does the		he project	is located	have a comp	prehensi	ve plan cons	sistent wit	h the C	Growth
Management Program? Ye	s □ No □. If n	o, the pro		mpt.		1			
If yes, local zoning ordinances a	and/or permits are	needed.		Approved [
☒ Maine Department of Inl						at			
Eagle Nest	N/A⊠	Applicat Applicat		Approved I					
Piping Plov Roseate Ter		Applicat		Approved I					
Roseate Tel	1 17/1	пррисас	лсш	Approved	_				
図 United States Fish and W	ildlife Service (U	USFWS),	Migrator	v Bird Act					
	pplicable		J	•					
☒ Maine Department of Co		ic Lands	, Submerg	ged Land Le	ease				
N/A ⊠ A	pplicable ⊔								
区 Land Use Regulation Com	mission (LUDC) 🔼 V	Int Applied	hla					
	o permit		ot Applica	ibie					
	otice			Approved [п				
	ermit			Approved [
				11					
⊠ Maine Department of 1	Environmental I	Protection	n (MDEP)	, Natural Ro	esource	Protection	Act		
	o permit required								
	xempt \square	(Must us	se erosion a	and sedimen		and not blo	ock fish pa	assage.))
	BR 🗵			Approved I					
	ier 1 🔲			Approved I					
	ier 2			Approved I					
11	ier 3 \square			Approved [Ш				
☒ Army Corps of Engineers	(ACOE), Section	n 10 of th	e Rivers a	nd Harbors	S Act and	d Section 40	04 of the	Clean '	Water Act.
		_							
	o permit required	Ш		A 17	[[]				
	ategory 1-NR⊠			Approved I					
	ategory 2□ ategory 3□			Approved I					
C				. ippioved i	_				

IN-WATER TIMING RESTRICTIONS: 105 Special Provision
■ Dates instream work is allowed: 7/15 – 10/1

n/a □

 [∑] Special Provision 656, Erosion Control Plan

 * Boxes marked in red indicate items that are attached and need to be placed in the contract by the Project Manager.

DEPARTMENT OF ENVIRONMENTAL PROTECTION (DEP) PERMIT BY RULE NOTIFICATION FORM

(For use with DEP Regulation, Chapter 305)

■ MDOT PIN: 11475.00

County: Washington

Name of Applicant: State of Maine Department of Transportation

Mailing Address: 16 Station State House
Daytime Telephone #: (207)-624-3105

Name of Wetland, Water Body or Stream: Lindsey Brook

Detailed Directions to Site: Project is on Rte 6 and is located 0.44 of a mile easterly of Route 1.

□Yes

Town/City: Topsfield

Part of a larger project?

☐Sec. (7) Outfall Pipes

Map #: N/A

(CHECK ONE) This project...

does □ does not ...involve work below mean low water.

Description of Project: Project scope is a culvert replacement with ancillary activity. The project will be performed in accordance with erosion control measures conforming with the latest versions of the State of Maine Department of Transportation Standard Specifications for Highways and Bridges and the Department of Transportation's Best Management Practices for Erosion and Sediment Control.

Lot #: N/A

□Sec. (13) F&W Creation/Enhance/Water Quality Improvement

am filing notice of my intent to carry ou DEP Regulation, Chapter 305. I have a with all of the standards.		
□Sec. (2) Soil Disturbance	☐Sec. (8) Shoreline stabilization	□Sec. (14) Piers, Wharves & Pilings
□Sec. (3) Intake Pipes	□Sec. (9) Utility Crossing	☐Sec. (15) Public Boat Ramps
☐Sec. (4) Replacement of Structures	□Sec. (10) Stream Crossing	☐Sec. (16) Coastal Sand Dune Project
□Sec. (5) REPEALED	⊠Sec. (11) State Transport. Facilities	☐Sec. (17) Transfers/Permit Extension
☐Sec. (6) Movement of Rocks or Vegetation	□Sec. (12) Restoration of Natural Areas	☐Sec. (18) Maintenance Dredging

I authorize staff of the Departments of Environmental Protection, Inland Fisheries & Wildlife, and Marine Resources to access the project site for the purpose of determining compliance with the rules. I also understand that this permit is not valid until approved by the Department or 14 days after receipt by the Department, whichever is less.

I have attached all of the following required submittals. NOTIFICATION FORMS CANNOT BE ACCEPTED WITHOUT THE NECESSARY ATTACHMENTS:

A \$50 (non-refundable) payment shall be done by internal billing.

■ Attach a U.S.G.S. topo map or Maine Atlas & Gazetteer map with the project site clearly marked.

Attach photographs showing existing site conditions (unless not required under standards).

Signature of Applicant: John E. Dority, Chief Engineer Date: 10/17/53

Keep the bottom copy as a record of permit. Send the form with attachments via certified mail to the Maine Dept. of Environmental Protection at the appropriate regional office listed below. The DEP will send a copy to the Town Office as evidence of the DEP's receipt of notification. No further authorization by DEP will be issued after receipt of notice. Permits are valid for two years. Work carried out in violation of any standard is subject to enforcement action.

AUGUSTA DEP STATE HOUSE STATION 17 AUGUSTA, ME 04333-0017 (207)287-2111 PORTLAND DEP 312 CANCO ROAD PORTLAND, ME 04103 (207)822-6300 BANGOR DEP 106 HOGAN ROAD BANGOR, ME 04401 (207)941-4570 PRESQUE ISLE DEP 1235 CENTRAL DRIVE PRESQUE ISLE, ME 04769 (207)764-0477

OFFICE USE ONLY Ck.# Staff Staff
PBR # FP Date Acc. Date Def. Date After Photos

Chapter 305: PERMIT BY RULE Section 11 State Transportation Facilities

1. Introduction. A "permit by rule" or "PBR", when approved by the Department of Environmental Protection (DEP), is an approval for an activity that requires a permit under the Natural Resources Protection Act (NRPA). Only those activities described in this chapter may proceed under the PBR process. A PBR activity will not significantly affect the environment if carried out in accordance with this chapter, and generally has less of an impact on the environment than an activity requiring an individual permit. A PBR satisfies the Natural Resources Protection Act (NRPA) permit requirement and Water Quality Certification requirement.

If a proposed activity is not described in this chapter, or will not be conducted in accordance with the standards of this chapter, the applicant must obtain an individual permit prior to beginning the activity.

- **A.** Location of activity. The location of an activity may affect whether an activity qualifies for PBR, and whether review by the Department of Inland Fisheries and Wildlife is required.
 - (1) Type of resource. For some types of activities, the availability of a PBR is affected by the type of natural resource in or adjacent to which the activity is proposed. For example, an applicant proposing an activity consisting of "Movement of rocks or vegetation" may receive a PBR only if the activity will take place in a great pond, river, stream or brook. Limitations concerning the location of activities are addressed in the "Applicability" provision in each section of this chapter.
 - (2) Essential habitat. Essential habitats include areas critical to the survival of threatened and endangered species such as the bald eagle, least tern, roseate tern, and piping plover. If the activity is located in essential habitat, such as near an eagle nesting site, a PBR is only available if the applicant obtains written approval from the Department of Inland Fisheries and Wildlife (IF&W). This approval from IF&W must be submitted to the DEP with the PBR notification form, and the applicant must follow any conditions stated in the IF&W approval.
- NOTE: Maps showing areas of essential habitat are available from the Department of Inland Fisheries and Wildlife regional headquarters, municipal offices, the Land Use Regulation Commission (for unorganized territories) and DEP regional offices. If the activity is located in essential habitat, IF&W must be contacted to request and obtain a "certification of review and approval".
- **B.** Notification. The applicant must file notice of the activity with the DEP prior to beginning work on the activity. The notification must be on a form provided by the DEP and must include any submissions required in this chapter. The applicant must keep a copy to serve as the permit.

The notification form must be sent to the DEP by certified mail (return receipt requested), or hand delivered to the DEP and date stamped by the department.

C. Effective period

(1) Beginning of period. The PBR becomes effective 14 calendar days after the DEP receives the notification form, unless the DEP approves or denies the PBR prior to that date. If the DEP does not speak with or write to the applicant within this 14 day period regarding the PBR notification, the applicant may proceed to carry out the activity.

There are three exceptions regarding the effective date of an approved PBR:

- (a) Activities listed in Section 10 (Stream crossings) occurring in association with forest management are exempt from the 14 day waiting period.
- (b) Activities listed in Section 2 (Soil disturbance) and Section 10 (Stream crossings) performed or supervised by individuals currently certified in erosion control practices by the DEP are exempt from the 14 day waiting period. To be certified in erosion control practices, an individual must successfully complete all course requirements of the Voluntary Contractor Certification Program administered by the DEP's Nonpoint Source Training and Resource Center.
- (c) Activities that are part of a larger project requiring a permit under the Site Location of Development or the Storm Water Management Acts may not proceed until any required permit under those laws is obtained.
- NOTE: Activities that are part of a larger project may require other permits from the DEP also.

 These other laws may prohibit the start of construction of any part of the project unless a permit under that law is obtained. In these cases, while not a violation of this rule, starting work on a PBR approved activity would be a violation of those other applicable laws.
- (2) End of period. The PBR is generally effective for 2 years from the date of approval, except that a PBR for "Replacement of structures" under Section 4 is effective for 3 years.
- NOTE: Activities that qualify under this chapter may need to meet other local, state and federal requirements. Examples -- (1) If an activity extends below the low water line of a lake, coastal wetland or international boundary water, the applicant should contact the Bureau of Parks and Lands (287-3061) concerning possible lease or easement requirements, or (2) If an activity will involve work below the mean high water line in navigable waters of the United States, the applicant should contact the Army Corps of Engineers (623-8367).
- **D. Discretionary authority.** Notwithstanding compliance with the PBR applicability requirements and standards set forth in this chapter, the DEP may require an individual permit application to be filed in any case where credible evidence indicates that the activity:
 - (1) May violate the standards of the NRPA (38 M.R.S.A. Section 480-D);
 - (2) Could lead to significant environmental impacts, including cumulative impacts; or
 - (3) Could adversely impact a resource of special concern.

If an individual permit is required pursuant to this subsection, the DEP shall notify the applicant in writing within the 14 calendar day waiting period described in sub-section (C) above. When the DEP notifies an applicant than an individual permit is required, no work may be conducted unless and until the individual permit is obtained.

E. Violations. A violation of law occurs when a person, or his or her agent, performs or causes to be performed any activity subject to the NRPA without first obtaining a permit from the DEP, or acts contrary to the provisions of a permit. The person, his or her agent, or both, may be held

responsible for the violation. Commonly, the "person" is the landowner, and the "agent" is the contractor carrying out the activity. A violation occurs when:

- (1) An activity occurs that is not allowed under PBR, whether or not a PBR notification form has been filed with and/or approved by the DEP;
- (2) An activity occurs that is allowed under PBR, but a PBR for the activity has not become effective prior to the beginning of the activity; or
- (3) An activity occurs that is allowed under PBR and a PBR for the activity is in effect, but the standards specified in this chapter are not met.

See the "applicability" provision under each activity for rules concerning what activities are allowed under PBR. A PBR is only valid for the person listed on the notification form, or for his or her agent.

Each day that a violation occurs or continues is considered a separate offense. Violations are subject to criminal penalties and civil penalties of not less than \$100 nor more than \$10,000 for each day of that violation (38 M.R.S.A. Section 349).

NOTE: A local Code Enforcement Officer (CEO) may take enforcement action for a violation of the Natural Resources Protection Act if he or she is authorized to represent a municipality in District Court, and he or she has been certified as familiar with court procedures, 30-A M.R.S.A. Section 4452(7).

Chapter 305 Section 11

State transportation facilities

A. Applicability

- (1) This section applies to the maintenance, repair, reconstruction, rehabilitation, replacement or minor construction of a State Transportation Facility carried out by, or under the authority of, the Maine Department of Transportation or the Maine Turnpike Authority, including any testing or preconstruction engineering, and associated technical support services.
- (2) This section does not apply to an activity within a coastal sand dune system.

NOTE: The construction of a transportation facility other than roads and associated facilities may be subject to the Storm Water Management Law, 38 M.R.S.A. Section 420-D.

B. Standards

- (1) Photographs of the area to be altered by the activity must be taken before work on the site begins. The photographs must be kept on file and be made available at the request of the DEP.
- (2) The activity must be reviewed by the Department of Inland Fisheries and Wildlife, the Department of Marine Resources, the Atlantic Salmon Authority, and the DEP's Division of Environmental Assessment prior to the notification being filed with the DEP. The activity must be performed according to any recommendations from these authorities.
- (3) The activity must be performed in accordance with erosion control measures conforming with the State of Maine Department of Transportation Standard Specifications for Highways and Bridges Revision of April 1995 and with the Department of Transportation's Best Management Practices for Erosion and Sediment Control, September 1997.

NOTE: Guidance on the use of erosion control best management practices can be obtained from the on site Construction Manager.

- (4) Alignment changes may not exceed a distance of 200 feet between the old and new center lines in any natural resource.
- (5) The activity may not alter more than 300 feet of shoreline (both shores added together) within a mile stretch of any river, stream or brook, including any bridge width or length of culvert.
- (6) The activity may not alter more than 150 feet of shoreline (both shores added together) within a mile stretch of any outstanding river segment identified in 38 M.R.S.A. 480-P, including any bridge width or length of culvert.
- (7) The activity must minimize wetland intrusion. The activity is exempt from the provisions of Chapter 310, the Wetland Protection Rules, if the activity alters less than 15,000 square feet of natural resources per mile of roadway (centerline measurement) provided that the following impacts are not exceeded within the 15,000 square foot area:

- (a) 1,000 square feet of coastal wetland consisting of salt tolerant vegetation or shellfish habitat; or
- (b) 5,000 square feet of coastal wetland not containing salt tolerant vegetation or shellfish habitat; or
- (c) 1,000 square feet of a great pond.

All other activities must be performed in compliance with all sections of Chapter 310, the Wetland Protection Rules, except 310.2(C), 5(A), 9(1), 9(B) and 9(C).

- (8) The activity may not permanently block any fish passage in any watercourse containing fish. The applicant must improve passage beyond what restriction may already exist unless the Department of Inland Fisheries and Wildlife, the Department of Marine Resources, the Atlantic Salmon Authority and the DEP's Division of Environmental Assessment concur that the improvement is not necessary.
- (9) Rocks may not be removed from below the normal high water line of any coastal wetland, freshwater wetland, great pond, river, stream or brook except to the minimum extent necessary for completion of work within the limits of construction.
- (10) If work is performed in a river, stream or brook that is less than three feet deep at the time and location of the activity, with the exception of culvert installation, the applicant must divert flow away from the activity while work is in progress.
 - (a) Diversion may be accomplished by the use of stable, inert material. No more than two thirds (2/3) of stream width may be diverted at one time.
 - (b) Any material used to divert water flow must be completely removed upon completion of the activity, and the stream bottom must be restored to its original condition.
 - (c) A pump may be operated, where necessary, for a temporary diversion. The pump outlet must be located and operated such that erosion or the discharge of sediment to the water is prevented.

NOTE: Guidance on the appropriate location of a diversion and materials which should be used for a stream diversion can be obtained from the on site Construction Manager.

- (11) Wheeled or tracked equipment may not operate in the water. Equipment operating on the shore may reach into the water with a bucket or similar extension. Equipment may cross streams on rock, gravel or ledge bottom.
- (12) All wheeled or tracked equipment that must travel or work in a vegetated wetland area must travel and work on mats or platforms.
- (13) Any debris or excavated material must be stockpiled either outside the wetland or on mats or platforms. Hay bales or silt fence must be used, where necessary, to prevent sedimentation. Any debris generated during the activity must be prevented from washing downstream and must be removed from the wetland or water body. Disposal of debris must be in conformance with the Maine Hazardous Waste, Septage and Solid Waste Management Act, 38 M.R.S.A. Section 1301 et seq.

- (14) Work below the normal high water line of a great pond, river, stream or brook must be done at low water except for emergency work or work agreed to by the resource agencies listed in paragraph 2 above. Measures, such as a silt boom or staked fencing, must be employed to reduce and isolate turbidity.
- (15) Perimeter controls must be installed before the work starts. Disturbance of natural resources beyond the construction limits shown on the plans is not allowed under this rule.

NOTE: Guidance on the location of construction limits can be obtained from the on site Construction Manager.

- (16) The use of untreated lumber is preferred. Lumber pressure treated with chromated copper arsenate (CCA) may be used, provided it is cured on dry land in a manner that exposes all surfaces to the air for a period of at least 21 days prior to construction. Wood treated with creosote or pentachlorophenol may not be used where it will contact water.
- (17) A temporary road for equipment access must be constructed of crushed stone, blasted ledge, or similar materials that will not cause sedimentation or restrict fish passage. Such roads must be completely removed at the completion of the activity. In addition, any such temporary roads which are in rivers, streams or brooks, must allow for a passage of stormwater flows associated with a 10-year storm.
- (18) Soil may not be disturbed during any period when soils are saturated due to rain or snow melt, except as necessary to protect work in progress or as required for bridge maintenance activities. Areas where soils are saturated (i.e. water drips from the soil when squeezed by hand, or the soil is capable of being rolled into a rod 1/8th inch in diameter that does not crumble) must be immediately mulched if they are disturbed.
- (19) Disturbed soil must be protected within one week from the time it was last actively worked, and prior to any storm event, using temporary or permanent measures such as the placement of riprap, sod, mulch, erosion control blankets, or other comparable measures.
- (20) Hay bale or straw mulch, where used, must be applied at a rate of at least one bale per 500 square feet (1 to 2 tons per acre).
- (21) If mulch is likely to be moved because of steep slopes or wind exposure, it must be anchored with netting, peg and twine, binder or other suitable method and must be maintained until a catch of vegetation is established over the entire disturbed area.
- (22) In addition to the placement of riprap, sod, erosion control blankets or mulch, additional steps must be taken where necessary to prevent sedimentation of the water Evidence of sedimentation includes visible sheet, rill or gully erosion, discoloration of water by suspended particles and/or slumping of banks. Silt fences, staked hay bales and other sedimentation control measures, where planned for, must be in place prior to the commencement of an activity, but must also be installed whenever necessary to prevent erosion and sedimentation.

NOTE: Guidance on the location and proper installation of erosion control measures can be obtained from the on site Construction Manager.

- (23) Temporary erosion control measures must be maintained and inspected weekly until the site is permanently stabilized with vegetation or other permanent control measures. Erosion control measures must also be inspected immediately prior to and following storms.
- (24) Permanent erosion control measures protecting all disturbed areas must be implemented within 30 days from the time the areas were last actively worked, or for fall and winter activities by the following June 15, except where precluded by the type of activity (e.g. riprap, road surfaces, etc.). The permanent erosion control measures must be maintained.
- (25) The applicant shall immediately take appropriate measures to prevent erosion or sedimentation from occurring or to correct any existing problems, regardless of the time of year.
- (26) Non-native species may not be planted in restored areas.
- (27) Disposal of debris must be in conformance with Maine Hazardous Waste, Septage and Solid Waste Management Act, 38 M.R.S.A. Sections 1301 et seq.
- (28) Disturbance of vegetation must be avoided, if possible. Where vegetation is disturbed outside of the area covered by any road or structure construction, it must be reestablished immediately upon completion of the activity and must be maintained.
- (29) A vegetated area at least 25 feet wide must be established and maintained between any new stormwater outfall structure and the high water line of any open water body. A velocity reducing structure must be constructed at the outlet of the stormwater outfall that will create sheet flow of stormwater, and prevent erosion of soil within the vegetated buffer. If the 25 foot vegetated buffer is not practicable, the applicant must explain the reason for a lesser setback in writing. Approval from the DEP must be in writing and any recommendations must be incorporated into the activity.
- **C. Definitions.** The following terms, as used in this chapter, have the following meanings, unless the context indicates otherwise:
 - (1) Diversion. A rerouting of a river, stream or brook to a location outside of its established channel
 - (2) Fill. a. (verb) To put into or upon, supply to, or allow to enter a water body or wetland any earth, rock, gravel, sand, silt, clay, peat, or debris; b. (noun) Material, other than structures, placed in or immediately adjacent to a wetland or water body.
 - (3) Floodplain wetlands. Freshwater wetlands that are inundated with flood water during a 100-year flood event based on flood insurance maps produced by the Federal Emergency Agency or other site specific information.
 - (4) Riprap. Rocks that are fit into place, usually without mortar, on a slope as defined in the State of Maine, Department of Transportation, Standard Specifications for Highway and Bridges, revision of April 1995.

Permit No: GP-39 Effective Date: Sept. 29, 2000 Expiration Date: Sept. 29, 2005

Applicant: General Public, State of Maine

DEPARTMENT OF THE ARMY PROGRAMMATIC GENERAL PERMIT STATE OF MAINE

The New England District of the U.S. Army Corps of Engineers hereby issues a programmatic general permit (PGP) that expedites review of minimal impact work in coastal and inland waters 1 and wetlands within the State of Maine. Activities with minimal impacts, as specified by the terms and conditions of this general permit and on the attached DEFINITION OF CATEGORIES sheets, are either non-reporting (provided required local and state permits are received), or are reporting, to be screened by the Corps and Federal Resource Agencies for applicability under the general permit. This general permit does not affect the Corps individual permit review process or activities exempt from Corps jurisdiction.

Activities Covered: work and structures that are located in, or that affect, navigable waters of the United States (regulated by the Corps under Section 10 of the Rivers and Harbors Act of 1899) and the discharge of dredged of fill material into waters of the United States (regulated by the Corps under Section 404 of the Clean Water Act), and the transportation of dredged material for the purpose of disposal in the ocean (regulated by the Corps under Section 103 of the Marine Protection, Research and Sanctuaries Act).

PROCEDURES:

A. State Approvals

For projects authorized pursuant to this general permit that are also regulated by the State of Maine, the following state approvals are also required and must be obtained in order for this general permit authorization to be valid (applicants are responsible for ensuring that all required state permits and approval have been obtained):

- (a) Maine Department of Environmental Protection (DEP): Natural Resources Protection Act permit, including permit-by-rule and general permit authorizations; Site Location and Development Act permit; and Maine Waterway Development and Conservation Act.
- (b) Maine Department of Conservation: Land Use Regulation Commission (LURC) permit.
- (c) Maine Department of Marine Resources: Lease.
- (d) Bureau of Public Lands, Submerged Lands: Lease.

Note that projects not regulated by the State of Maine (e.g., seasonal floats or moorings) may still be authorized by this general permit.

B. Corps Authorizations: Category I (Non-Reporting)

Work in Maine subject to Corps jurisdiction that meets the definition of Category I on the attached DEFINITION OF CATEGORIES sheets and that meets all of this permit's other conditions, does not require separate application to the Corps of Engineers. If the State or the Corps does not contact the applicant for PBRs and Tier One permits during the State's Tier One 30-day review period, Corps approval may be assumed and the project may proceed. Refer to the Procedures Section at Paragraph E below for additional information regarding screening.

Note that the review thresholds under Category I apply to single and complete projects i only (see special condition 5). Also note that Category I does not apply to projects occurring in a component of, or within 0.25 miles up and downstream of the main stem or tributaries of a river segment of the National Wild and Scenic River System (see condition 11, and page 9 for the listed rivers in Maine).

There are also restrictions on other national lands or concerns, which must be met in order for projects to be eligible for authorization under this PGP. Refer to special conditions 6-13 under Paragraph F below.

Work that is not regulated by the State of Maine, but that is subject to Corps jurisdiction, is eligible for Corps authorization under this PGP in accordance with the review thresholds and conditions contained herein.

Although Category I projects are non-reporting, the Corps reserves the right to require screening or an individual permit review if there are concerns for the aquatic environment or any other factor of the public interest (see special condition 4 on Discretionary Authority). The Corps review or State/Federal screening process may also result in project modification, mitigation or other special conditions necessary to minimize impacts and protect the aquatic environment as a requirement for PGP approval.

C. Corps Authorization: Category II (Reporting - requiring screening) APPLICATION PROCEDURES

For projects that do not meet the terms of Category I (see DEFINITION OF CATEGORIES sheets), the Corps, State, and Federal Resource Agencies will conduct joint screening meetings to review applications. If projects are concurrently regulated by the DEP or LURC, applicants do not need to submit separate applications to the Corps. For projects not regulated by DEP or LURC, applicants must submit an application to the Corps Maine Project Office for a case-by-case determination of eligibility under this general permit (Category II). Category II projects may not proceed until written notification is received from the Corps.

Category II projects which occur in a component of, or within 0.25 mile up or downstream of the main stem or tributaries of a river segment of the National Wild and Scenic River System, will be coordinated with the National Park Service (see special condition 11, and page 9 for listed rivers in Maine).

There are also restrictions on other national lands or concerns, which must be met in order for projects to be eligible for authorization under this PGP. Refer to special conditions 6-14 under Paragraph E below.

Category II applicants shall submit a copy of their application materials to the Maine Historic Preservation Commission and/or applicable Indian tribe(s) at the same time, or before, they apply to the DEP, LURC, or the Corps so that the project can be reviewed for the presence of historic/archaeological resources in the project area that may be affected by the proposed work. Applications to the DEP or the Corps should include information to indicate that this has been done (applicant's statement or copy of cover letter to Maine Historic Preservation Commission and/or Indian tribe(s)).

The Corps may require additional information on a case-by-case basis as follows:

- (a) purpose of project;
- (b) 8 1/2" by 11" plan views of the entire property including property lines and project limits with existing and proposed conditions (legible, reproducible plans required);
- (c) wetland delineation for the site, information on the basis of the delineation, and calculations of waterway and wetland impact areas (see special condition 2);
- (d) typical cross-section views of all wetland and waterway fill areas and wetland replication areas;
- (e) delineation of submerged aquatic vegetation, e.g., eel grass beds, in tidal waters;
- (f) area, type and source of fill material to be discharged into waters and wetlands, including the volume of fill below ordinary high water in inland waters and below the high tide line in coastal waters;
- (g) mean low, mean high water and high tide elevations in navigable waters;
- (h) limits of any Federal navigation project in the vicinity and State Plane coordinates for the limits of the proposed work closest to the Federal project;
- (i) on-site alternatives analysis (contact Corps for guidance);
- (j) identify and describe potential impacts to Essential Fish Habitat (contact Corps for guidance);
- (k) for dredging projects, include:
- 1) the volume of material and area in square feet to be dredged below mean high water,
- 2) existing and proposed water depths,
- 3) type of dredging equipment to be used,
- 4) nature of material (e.g., silty sand),

- 5) any existing sediment grain size and bulk sediment chemistry data for the proposed or any nearby projects,
- 6) information on the location and nature of municipal or industrial discharges and occurrences of any contaminant spills in or near the project area,
- 7) location of the disposal site (include locus sheet),
- 8) shellfish survey, and
- 9) sediment testing, including physical, chemical and biological testing. For projects proposing open water disposal, applicants are encouraged to contact the Corps as early as possible regarding sampling and testing protocols.

The Corps may request additional information. Dredging applicants may be required to conduct a shellfish and/or eel grass survey and sediment testing, including physical, chemical and biological testing. Sediment sampling and testing plans should be prepared or approved by the Corps before the samples are collected.

STATE-FEDERAL SCREENING PROCEDURES:

The Corps intends to utilize the application information required by the State for its regulatory program to the maximum extent practicable and the Corps normally will not be interacting with an applicant who is concurrently making application to the DEP or LURC. Projects not regulated by the State, but needing Corps of Engineers approval, **must apply directly to the Corps.** The joint screening meeting for Category II projects will occur regularly at the Corps or State of fices and will involve representatives from the DEP, the Corps, the U.S. Environmental Protection Agency, the U.S. Fish and Wildlife Service, and the National Marine Fisheries Service.

The Corps and Federal Resource Agencies will classify the project within the State's review period, not to exceed 60 days, as: 1) approvable under the PGP as proposed; 2) needs additional information, including possible project modification, mitigation or other special conditions to minimize impacts; or 3) exceeds the terms or conditions of the PGP, including the minimal effects requirement, and an individual permit review will be required. In addition, the Corps retains the ability to exercise its discretionary authority and require an individual permit, irrespective of whether the terms and conditions of this general permit are met, based on concerns for the aquatic environment or any factor of the public interest (see special condition 4 on Discretionary Authority). All Category II projects must receive written approval from the Corps before work can proceed. If the project is not approvable as proposed, the DEP, LURC, or the Corps will contact the applicant to discuss the concerns raised. If the applicant is unable to resolve the concerns, the Corps, independently or at the request of the Federal Resource Agencies, will require an individual permit for the project. The applicant will be notified of this in writing, along with information about submitting the necessary application materials. The comments from the Federal Resource Agencies to the Corps may be verbal initially, and must be made within 10 working days of the screening meeting. These comments must be confirmed in writing within 10 calendar days of the verbal response if the Resource Agency(ies) will request an individual permit. The Federal Resource Agency's comments must reflect a concern within their area of expertise, state the species or resources that could be impacted by the project, and describe the impacts that either individually or cumulatively will be more than minimal.

MINERALS MANAGEMENT SERVICE (MMS) REVIEW

For Category II projects which involve construction of solid fill structures or discharge of fills along the coast which may extend the coastline or baseline from which the territorial sea is measured, coordination between the Corps and Minerals Management Service (MMS), Continental Shelf (OCS) Survey Group, will be needed (pursuant to the Submerged Lands Act, 43 U.S.C., Section 1301-1315, 33 CFR 320.4(f). During the screening period, the Corps will forward project information to MMS for their review. MMS will coordinate their determination with the Department of the Interior (DOI) Solicitor's Office. The DOI will have 15 calendar days from the date MMS is in receipt of project information to determine if the baseline will be affected. No notification to the Corps within 15 day review period will constitute a "no affect" determination. Otherwise, the solicitor's notification to the Corps may be verbal but must be followed with a written confirmation within 10 business days from the date of the verbal notification. This procedure will be eliminated if the State of Maine provides a written waiver of interest in any increase in submerged lands caused by a change in the baseline resulting from solid fill structure or fills authorized under this general permit.

D. Corps Authorization: Category III (Individual Permit)

Work that is in the INDIVIDUAL PERMIT category on the attached DEFINITION OF CATEGORIES sheets, or that does not meet the terms and conditions of this general permit, will require an application for an individual permit from the Corps of Engineers (see 33 CFR Part 325.1). The screening procedures outlined above will only serve to delay project review in such cases. The applicant should submit the appropriate application materials (including the Corps application form) at the earliest possible date. General information and application forms can be obtained at (207) 623-8367 (Maine Field Office), (800) 343-4789, or (800) 362-4367 in Massachusetts. Individual water quality certification and coastal zone management consistency concurrence will be required from the State of Maine before Corps permit issuance.

E. Programmatic General Permit Conditions:

The following conditions apply to activities authorized under the PGP, including all Category I (non-reporting) and Category II (reporting - requiring screening) activities:

GENERAL REQUIREMENTS:

- 1. **Other Permits.** Authorization under this general permit does not obviate the need to obtain other Federal, state, or local authorizations required by law.
- 2. Applicability of this general permit shall be evaluated with reference to Federal jurisdictional boundaries. Applicants are responsible for ensuring that the boundaries used satisfy the federal criteria defined at 33 CFR 328-329.
- 3. **Minimal Effects.** Projects authorized by this general permit shall have minimal individual and cumulative adverse environmental impacts as determined by the Corps.

4. **Discretionary Authority.** Notwithstanding compliance with the terms and conditions of this permit, the Corps of Engineers retains discretionary authority to require review for an individual permit based on concerns for the aquatic environment or for any other factor of the public interest. This authority is invoked on a case-by-case basis whenever the Corps determines that the potential consequences of the proposal warrant individual review based on the concerns stated above. This authority may be invoked for projects with cumulative environmental impacts that are more than minimal or if there is a special resource or concern associated with a particular project that is not already covered by the remaining conditions of the PGP and that warrants greater review.

Whenever the Corps notifies an applicant that an individual permit may be required, authorization under this general permit is void and no work may be conducted until the individual Corps permit is obtained or until the Corps notifies the applicant that further review has demonstrated that the work may proceed under this general permit.

5. **Single and Complete Projects.** This general permit shall not be used for piecemeal work and shall be applied to single and complete projects. All components of a single project and/or all planned phases of multi-phased projects shall be treated together as constituting one single and complete project (e.g., subdivisions should include all work such as roads, utilities, and lot development). This general permit shall not be used for any activity that is part of an overall project for which an individual permit is required.

NATIONAL CONCERNS:

- 6. St. John/St. Croix Rivers. This covers work within the Saint John and Saint Croix River basins that requires approval of the International Joint Commission. This includes any temporary or permanent use, obstruction or diversion of international boundary waters which could affect the natural flow or levels of waters on the Canadian side of the line, as well as any construction or maintenance of remedial works, protective works, dams, or other obstructions in waters downstream from boundary waters when the activity could raise the natural level of water on the Canadian side of the boundary.
- 7. **Historic Properties.** Any activity authorized by this general permit shall comply with Section 106 of the National Historic Preservation Act. Information on the location and existence of historic resources can be obtained from the Maine Historic Preservation Commission and the National Register of Historic Places. Federally recognized tribes (Penobscots, Passamaquoddys, Micmacs, and Maliseets) may know of the existence of other sites that may be of significance to their tribes. See page 14 for historic properties contacts.

Applicants with projects which will undergo the screening process (Category II) shall submit a copy of their application materials, with the name and address of the applicant clearly indicated, to the Maine Historic Preservation Commission, 55 Capitol Street, State House Station 65, Augusta, Maine 04333, and to the applicable tribe(s) to be reviewed for the presence of historic and/or archaeological resources in the permit area that may be affected by the proposed work. The Corps will then be notified by the Commission and/or

Tribe within 10 days if there are State and/or tribal concerns that the proposed work will have an effect on historic resources. The applicant should include with their application to the State or the Corps either a copy of their cover letter or a statement of having sent their application material to the Commission and Tribe(s).

If the permittee, either prior to construction or during construction of the work authorized herein, encounters a previously unidentified archaeological or other cultural resource, within the area subject to Department of the Army jurisdiction, that might be eligible for listing in the National Register of Historic Places, he/she shall stop work and immediately notify the District Engineer and the Maine Historic Preservation Commission and/or applicable Tribe(s).

- 8. **National Lands.** Activities authorized by this general permit shall not impinge upon the value of any National Wildlife Refuge, National Forest, or any area administered by the National Park Service.
- 9. Endangered Species. No activity is authorized under this general permit which
- may affect a threatened or endangered species or a species proposed for such designation as identified under the Federal Endangered Species Act (ESA),
- is likely to destroy or adversely modify the critical habitat or proposed critical habitat of such species,
- would result in a 'take' of any threatened or endangered species of fish or wildlife, or
- would result in any other violation of Section 9 of the ESA protecting threatened or endangered species of plants.

Applicants shall notify the Corps if any listed species or critical habitat, or proposed species or critical habitat, is in the vicinity of the project and shall not begin work until notified by the District Engineer that the requirements of the Endangered Species Act have been satisfied and that the activity is authorized. Information on the location of threatened and endangered species and their critical habitat can be obtained from the U.S. Fish and Wildlife Service and National Marine Fisheries Service (addresses attached, page 14).

10. **Essential Fish Habitat.** As part of the PGP screening process, the Corps will coordinate with the National Marine Fisheries Service (NMFS) in accordance with the 1996 amendments to the Magnuson-Stevens Fishery and Conservation Management Act to protect and conserve the habitat of marine, estuarine and anadromous finfish, mollusks, and crustaceans. This habitat is termed "essential fish habitat (EFH)", and is broadly defined to include "those waters and substrate necessary to fish for spawning, breeding, feeding, or growth to maturity." Applicants may be required to describe and identify potential impacts to EFH based upon the location of the project, the activity proposed, and the species present. Conservation recommendations made by NMFS will normally be included as a permit requirement by the Corps. Information on the location of EFH can be obtained from the NMFS regulations (50 CFR Part 600) (address listed on page 14) and on their web site (http://www.nero.nmfs.gov/ro/doc/webintro.html).

The EFH designation for Atlantic salmon includes all aquatic habitats in the watershed of the following rivers and streams, including all tributaries to the extent that they are currently or were historically accessible for salmon migration:

St. Croix River PleasantRiver UnionRiver Boyden River Narraguagus River **Ducktrap** River **Dennys River** Tunk Stream Sheepscot River Hobart Stream Patten Stream Kennebec River Aroostook River Orland River Androscoggin River Presumpscot River East Machias River Penobscot River

Machias River Passagassawaukeag River Saco River

- 11. Wild and Scenic Rivers. Any activity that occurs in a component of, or within 0.25 mile up or downstream of the main stem or tributaries of a river segment of the National Wild and Scenic River System, must be reviewed by the Corps under the procedures of Category II of this general permit regardless of size of impact. This condition applies to both designated wild and scenic rivers and rivers designated by Congress as study rivers for possible inclusion while such rivers are in an official study status. The Corps will consult with the National Park Service (NPS) with regard to potential impacts of the proposed work on the resource values of the Wild and Scenic River. The culmination of this coordination will be a determination by the NPS and the Corps that the work: (1) may proceed as proposed; (2) may proceed with recommended conditions; or (3) could pose a direct and adverse effect on the resource values of the river and an individual permit is required. If pre-application consultation between the applicant and the NPS has occurred whereby the NPS has made a determination that the proposed project is appropriate for authorization under this PGP (with respect to wild and scenic river issues), this determination should be furnished to the Corps with submission of the application. The address of the NPS can be found on Page 14 of this permit. National Wild/Scenic Rivers System (Designated River in Maine) as of 5/2/00: Allagash River beginning at Telos Dam continuing to Allagash checkpoint at Eliza Hole Rapids, approximately 3 miles upstream of the confluence with the St. John River. Length = 92 miles
- 12. **Federal Navigation Project.** Any structure or work that extends closer to the horizontal limits of any Corps navigation project than a distance of three times the project's authorized depth (see attached map following page 16 for locations of these projects) shall be subject to removal at the owner's expense prior to any future Corps dredging or the performance of periodic hydrographic surveys.
- 13. **Navigation.** There shall be no unreasonable interference with navigation by the existence or use of the activity authorized herein and no attempt shall be made by the permittee to prevent the full and free use by the public of all navigable waters at or adjacent to the activity authorized herein.

The permittee understands and agrees that, if future operations by the United States require the removal, relocation, or other alteration, of the structure or work herein authorized, or if, in the opinion of the Secretary of the Army or his authorized representative, said structure

or work shall cause unreasonable obstruction to the free navigation of the navigable waters, the permittee will be required, upon due notice from the Corps of Engineers, to remove, relocate, or alter the structural work or obstructions caused thereby, without expense to the United States. No claim shall be made against the United States on account of any such removal or alteration.

14. **Federal Liability.** In issuing this permit, the Federal Government does not assume any liability for the following: (a) damages to the permitted project or uses thereof as a result of other permitted or unpermitted activities or from natural causes; (b) damages to the permitted project or uses thereof as a result of current or future activities undertaken by or on behalf of the United States in the public interest; (c) damages to persons, property, or to other permitted or unpermitted activities or structures caused by the activity authorized by this permit; (d) design or construction deficiencies associated with the permitted work; (e) damage claims associated with any future modification, suspension, or revocation of this permit.

MINIMIZATION OF ENVIRONMENTAL IMPACTS:

- 15. **Minimization.** Discharges of dredged or fill material into waters of the United States shall be avoided and minimized to the maximum extent practicable, regardless of review category.
- 16. Work in Wetlands. Heavy equipment working in wetlands shall be avoided if possible, and if required, shall be placed on mats or other measures taken to minimize soil and vegetation disturbance. Disturbed areas in wetlands shall be restored to preconstruction contours and conditions upon completion of the work.
- 17. **Temporary Fill.** Temporary fill in waters and wetlands authorized by this general permit (e.g., access roads, cofferdams) shall be properly stabilized during use to prevent erosion. Temporary fill in wetlands shall be placed on geotextile fabric laid on existing wetland grade. Temporary fills shall be disposed of at an upland site, suitably contained to prevent erosion and transport to a waterway or wetland. Temporary fill areas shall be restored to their approximate original contours but not higher. No temporary fill shall be placed in waters or wetlands unless specifically authorized by the Corps.
- 18. **Sedimentation and Erosion Control.** Adequate sedimentation and erosion control management measures, practices and devices, such as phased construction, vegetated filter strips, geotextile silt fences or other devices, shall be installed and properly maintained to reduce erosion and retain sediment on-site during and after construction. They shall be capable of preventing erosion, of collecting sediment, suspended and floating materials, and of filtering fine sediment. These devices shall be removed upon completion of work and the disturbed areas shall be stabilized. The sediment collected by these devices shall be removed and placed at an upland location in a manner that will prevent its later erosion into a waterway or wetland. All exposed soil and other fills shall be permanently stabilized at the earliest practicable date.

19. Waterway Crossings.

- (a) All temporary and permanent crossings of waterbodies shall be suitably culverted, bridged, or otherwise designed to withstand and to prevent the restriction of high flows, to maintain existing low flows, and to not obstruct the movement of aquatic life indigenous to the waterbody beyond the actual duration of construction.
- (b) Temporary bridges, culverts, or cofferdams shall be used for equipment access across streams (NOTE: areas of fill and/or cofferdams must be included in total waterway/wetlands impacts to determine applicability of this general permit).
- (c) For projects that otherwise meet the terms of Category I, instream construction work shall be conducted during the low flow period July 15 October 1 in any year. Projects that are not to be conducted during that time period are ineligible for Category I and shall be screened pursuant to Category II, regardless of the waterway and wetland fill and/or impact area.
- 20. **Discharge of Pollutants.** All activities involving any discharge of pollutants into waters of the United States authorized under this general permit shall be consistent with applicable water quality standards, effluent limitations, standards of performance, prohibitions, and pretreatment standards and management practices established pursuant to the Clean Water Act (33 U.S.C. 1251) and applicable state and local laws. If applicable water quality standards, limitations, etc., are revised or modified during the term of this permit, the authorized work shall be modified to conform with these standards within six months of the effective date of such revision or modification, or within a longer period of time deemed reasonable by the District Engineer in consultation with the Regional Administrator of the Environmental Protection Agency. Applicants may presume that state water quality standards are met with issuance of the 401 Water Quality Certification.
- 21. **Spawning Areas.** Discharges into known 1) fish and shellfish spawning or nursery areas; and 2) amphibian and waterfowl breeding areas, during spawning or breeding seasons shall be avoided, and impacts to these areas shall be avoided or minimized to the maximum extent practicable during all times of year.
- 22. **Storage of Seasonal Structures.** Coastal structures such as pier sections and floats that are removed from the waterway for a portion of the year shall be stored in an upland location located above mean high water and not in tidal marsh.
- 23. **Environmental Values.** The permittee shall make every reasonable effort to carry out the construction or operation of the work authorized herein in a manner so as to maintain as much as is practicable, and to minimize any adverse impacts on, existing fish and wildlife and natural environmental values.
- 24. **Protection of Vernal Pools.** Impacts to uplands in proximity (within 500 feet) to the vernal pools referenced in DEFINITIONS OF CATEGORIES shall be minimized to the maximum extent possible.

PROCEDURAL CONDITIONS:

25. **Cranberry Development Projects.** For Cranberry development projects authorized under the PGP, the following conditions apply:

4

- 1. If a cranberry bog is abandoned for any reason, the area must be allowed to convert to natural wetlands unless an individual permit is obtained from the Corps of Engineers allowing the discharge of fill for an alternate use.
- 2. No stream diversion shall be allowed under this permit.
- 3. No impoundment of perennial streams shall be allowed under this permit.
- 4. The project shall be designed and constructed to not cause flood damage on adjacent properties.
- 26. Inspections. The permittee shall permit the District Engineer or his authorized representative(s) to make periodic inspections at any time deemed necessary in order to ensure that the work is being performed in accordance with the terms and conditions of this permit. The District Engineer may also require post-construction engineering drawings for completed work, and post-dredging survey drawings for any dredging work. To facilitate these inspections, the attached work notification form should be filled out and returned to the Corps for all Category II projects.
- 27. Maintenance. The permittee shall maintain the work or structures authorized herein in good condition, including maintenance, to ensure public safety. Dredging projects: note that this does not include maintenance of dredging projects. Maintenance dredging is subject to the review thresholds described on the attached DEFINITION OF CATEGORIES sheets and/or any conditions included in a written Corps authorization.
- 28. Property Rights. This permit does not convey any property rights, either in real estate or material, or any exclusive privileges, nor does it authorize any injury to property or invasion of rights or any infringement of federal, state, or local laws or regulations. If property associated with work authorized by the PGP is sold, the PGP authorization is automatically transferred to the new property owner. The new property owner should provide this information to the Corps in writing. No acknowledgement from the Corps is necessary.
- 29. **Modification, Suspension, and Revocation.** This permit may be either modified, suspended, or revoked, in whole or in part, pursuant to the policies and procedures of 33 CFR 325.7 and any such action shall not be the basis for any claim for damages against the United States.
- 30. **Restoration.** The permittee, upon receipt of a notice of revocation of authorization under this permit, shall restore the wetland or waterway to its former condition without expense to the United States and as directed by the Secretary of the Army or his authorized representative. If the permittee fails to comply with such a directive, the Secretary or his designee may restore the wetland or waterway to its former condition, by contract or otherwise, and recover the cost from the permittee.

- 31. **Special Conditions.** The Corps, independently or at the request of the Federal Resource Agencies, may impose other special conditions on a project authorized pursuant to this general permit that are determined necessary to minimize adverse environmental effects or based on any other factor of the public interest. Failure to comply with all conditions of the authorization, including special conditions, will constitute a permit violation and may subject the permittee to criminal, civil, or administrative penalties or restoration.
- 32. **False or Incomplete Information.** If the Corps makes a determination regarding the eligibility of a project under this permit and subsequently discovers that it has relied on false, incomplete, or inaccurate information provided by the permittee, the permit shall not be valid and the government may institute appropriate legal proceedings.
- 33. **Abandonment.** If the permittee decides to abandon the activity authorized under this general permit, unless such abandonment is merely the transfer of property to a third party, he/she must restore the area to the satisfaction of the District Engineer.
- 34. **Enforcement cases.** This general permit does not apply to any existing or proposed activity in Corps jurisdiction associated with an on-going Corps of Engineers or Environmental Protection Agency enforcement action until such time as the enforcement action is resolved or the Corps determines that the activity may proceed independently without compromising the enforcement action. The Corps may choose not to accept applications or issue permits to any applicant with outstanding violations.
- 35. **Emergency situations.** This PGP can be used to authorize the repair, rehabilitation, or replacement of those structures destroyed by storms, floods, fire or other discrete unexpected and catastrophic event. In such situations and if the work exceeds Category I limitations, if applicant applies to the Corps within 30 days of the event, the Corps will attempt to contact the resource agencies for their approvals but, if unable to contact them, will issue an emergency permit and review them after-the-fact with the agencies at the next joint processing meeting. Proposed work submitted more than 30 days after the emergency will go through the standard PGP procedures.

DURATION OF AUTHORIZATION/GRANDFATHERING:

36. **Duration of Authorization.** Activities authorized under this general permit that have commenced (i.e., are under construction) or are under contract to commence in reliance upon this authorization will remain authorized provided the activity is completed within twelve months of the date of the general permit's expiration, modification, or revocation, unless discretionary authority has been exercised on a case-by-case basis to modify, suspend, or revoke the authorization in accordance with 33 CFR 325.2 (e)(2). Activities completed under the authorization of the general permit that was in effect at the time the activity was completed will continue to be authorized by the general permit.

37. Previously Authorized Activities.

- (a) Activities which have commenced (i.e., are under construction or are under contract to commence) prior to the issuance date of this general permit, in reliance upon the terms and conditions of the non-reporting category of the previous Maine PGP shall remain authorized provided the activity is completed within twelve months of the date of issuance of this general permit, unless discretionary authority has been exercised on a case-by-case basis to modify, suspend, or revoke the authorization in accordance with special condition 4. The applicant must be able to document to the Corps satisfaction that the project was under construction or contract by the appropriate date.
- (b) Projects that have received written verification or approval from the Corps, based on applications made to the Corps prior to issuance of this general permit, for the previous Maine SPGP and PGP, Nationwide permits, regional general permits, or letters of permission shall remain authorized as specified in each authorization.
- (c) This general permit does not affect activities authorized pursuant to 33 CFR Part 330.3 (activities occurring before certain dates).

For DISTRICT ENGINEER Christine Gedfrey DATE 7 / 26 / 00

CONTACTS FOR MAINE PROGRAMMATIC GENERAL PERMIT:

U.S. Army Corps of Engineers
Maine Project Office
675 Western Avenue #3
Manchester, Maine 04351
207-623-8367
Fax # 207-623-8206

Federal Endangered Species
U.S. Fish and Wildlife Service
Maine Field Office
1033 South Main Street
Old Town, Maine 04468
207-827-5938
Fax # 207-827-6099

Wild and Scenic Rivers National Park Service North Atlantic Region 15 State Street Boston, MA 02109 617-223-5203

Maine Historic Preservation Commission
55 Capitol Street
State House Station 65
Augusta, Maine 04333
207-287-2132
Fax # 207-287-2335
Aroostook Band of Micmacs
P.O. Box 772
Presque Isle, Maine 04769
207-764-1972
Fax # 207-764-7667

Passamaquoddy Tribe of Indians Pleasant Point Reservation Attn: Tribal Council P.O. Box 343 Perry, Maine 04667 207-853-2600 Fax # 207-853-6039 Federal Endangered Species and Essential Fish Habitat National Marine Fisheries Service One Blackburn Drive Gloucester, Massachusetts 01939 978-281-9102 Fax # 978-281-9301

Houlton Band of Maliseet Indians
Attn: Brenda Commander, Tribal Chief
Route 3 - Box 450
Houlton, Maine 04730
207-532-4273
Fax # 207-532-2660
Passamaquoddy Tribe of Indians
Indian Township Reservation
Attn: Donald Soctomah
P.O. Box 301
Princeton, Maine 04668
207-796-2301
Fax # 207-796-5256

Penobscot Indian Nation Richard Hamilton, Chief 6 River Road Indian Island Reservation Old Town, Maine 04468 (207) 827-7776 Fax # 207-827-1137

29/00 14

Maine Department of Environmental Protection (For State Permits and Water Quality *Certifications*) Natural Resources Division Bureau of Land and Water Quality Control State House Station 17 Augusta, Maine 04333 207-287-2111

Eastern Maine Regional Office 106 Hogan Road Bangor, Maine 04401 207-941-4570

MaineLand UseRegulation Commission (LURC) offices 22 State House Station Augusta, ME 04333-0022 207-287-2631 800-452-8711 (call to obtain appropriate LURC of fice) Fax # 207-287-7439

Lakeview Drive P.O.BoxllO7 Greenville, ME 04441 207-695-2466 Fax # 207-695-2380

i

(For CZMDeterminations) State Planning Office Coastal Program 184 State Street **State House Station 38** Augusta, Maine 04333 207-287-1009

(For Submerged Lands Leases) Maine Department of Conservation Bureau of Parks and Lands 22 State House Station 207-287-3061

9129/00

Southern Maine Regional Office 312 Canco Road Portland, Maine 04103 201-822-6300

Northern Maine Regional Office 1235 Central Drive Skyway Park Presque Isle, Maine 04769 207-764-0477

45 Radar Road Ashland.ME 04732-3600 207-435-7963 Fax # 207-435-7184

191 Main Street EastMillinocket,ME 04430 207-746-2244 Fax # 207-746-2243

Maine Department of Marine Resources (For Aquaculture Leases) McKown Point Boothbay Harbor, Maine 04575 207-633-9500

15

9/29/00 15

A. INLAND WETLANDS (WATERS OF THE U.S.) ¹	CATEGORY I	CATEGORY II	INDIVIDUAL PERMIT
(a) NEW FILL/ EXCAVATION DISCHARGES	Less than 4,300 sf inland waterway and /or wetland fill and secondary impacts (e.g., areas drained, flooded or cleared). Includes projects covered by a State Tier One permit with no cumulative impacts over 15,000 sf in inland wetlands from previous permits, unauthorized work, and/or other state permits. Includes crossing of perennial waterways designated as Essential Fish Habitat (EFH) for Atlantic salmon² if the waterway is crossed with a span and footprints of the span abutments are outside ordinary high water with no more than 4,300 sf of associated wetland impact. Includes in-stream work of up to 4,300 sf of fill below ordinary high water in waterways not designated as EFH for Atlantic salmon² and performed in accordance with Maine Permit By Rule standards or a LIRC permit	4,300 sf to 3 acres inland waterway and/or wetland fill and secondary impacts (e.g., areas drained, flooded or cleared). - Impact area includes all temporary and permanent fill and excavation discharges except for incidental fallback. - Includes in-stream work, including crossings (other than a spanned crossing as described in Category I) with any discharge of fill below ordinary high water in perennial waterways designated as EFH for Atlantic salmon? - Time of year restrictions determined case-by-case.	Greater than 3 acres inland waterway and/or wetland fill and secondary impacts (e.g., areas drained, flooded or cleared) Impact area includes all temporary and permanent fill and excavation discharges except for incidental fallback³. In-stream work exceeding Category II limits. If EIS required by the Corps.

¹ Water of the U.S. in inland areas: inland rivers, streams, lakes, ponds and wetlands.

Machias, Pleasant, Narraguagus, Tunk stream, Patten Stream, Orland, Penobscot, Passagassawaukeag, Union, Ducktrap, Sheepscot, Kennebec, Androscoggin, ² Essential Fish Habitat for Atlantic salmon includes all aquatic habitats in the watersheds of the following rivers and streams, including all tributaries to the extent that they are currently or were historically accessible for salmon migration: St. Croix, Boyden, Dennys, Hobart Stream, Aroostook, East Machias, Presumpscot and Saco River.

³ The larger the impacts, the more likely an individual permit will be required. Projects involving widening, expansion or impacts to degraded or low value wetlands between 1-3 acres may be approved under Category II, subject to the Federal screening. The Corps recognizes and endorses the DEP Tier 2 upper thresholds of 1 acre. Compensatory mitigation is likely to be required at this level of impact.

	CATEGORY I	CATEGORY II	INDIVIDUAL PERMIT
(a) NEW FILL/ EXCAVATION DISCHARGES	 Impact area includes all temporary and permanent fill and excavation discharges except for incidental fallback. In-stream work limited to July 15 - Oct. 1. This category excludes situations when a vernal pool of any size may be impacted, in accordance with the ME DEP definition of vernal pool4 This category excludes work within ¼ mile or a Wild and Scenic River5 This category excludes dams, dikes, or activities involving water withdrawal or water diversion. This category excludes work in National Wildlife Refuges. 	Proactive restoration projects with any amount of impact can be reviewed under Category II. The Corps, in consultation with State and Federal agencies, must determine that net adverse effects are not more than minimal.	
(b) BANK STABILIZATION PROJECTS	Inland bank stabilization less than 500 ft. long and less than 1 cy fill per linear foot below ordinary high water in ponds, lakes, and waterway not designated as EFH for Atlantic salmon², provided there is no wetland fill. In-stream work limited to July 15 - Oct. 1.	Inland bank stabilization in ponds, lakes, and waterways not designated as EFH for Atlantic salmon² which exceeds Category I limits. Inland bank stabilization of any size below ordinary high water in waterways designed as EFH for Atlantic salmon². Other stabilization exceeding Category I.	
(C) REPAIR AND MAINTENANCE OF AUTHORIZED FILLS	Repair or maintenance of existing, currently serviceable, authorized fills with no substantial expansion or change in use.	Replacement of non-serviceable fills, or repair or maintenance of serviceable fills with expansion of any amount up to 1 acre, or with a change in use.	Replacement of non-serviceable fills, or repair or maintenance of serviceable fills with greater than 1 acre of expansion.

4 Vernal Pool: Naturally-occurring, or intentionally created for the purposes of compensatory mitigation, temporary to permanent bodies of water occurring in shallow depressions that fill during the spring and fall and may dry during the summer. Vernal pools have no permanent or viable populations of predatory fish. Vernal pools provide the primary breeding habitat for wood frogs, spotted salamanders, blue-spotted salamanders, and fairy shrimp, and provide habitat for other wildlife including several endangered and threatened species.

5National Wild/Scenic Rivers System (Designated River in Maine): Allagash River beginning at Telos Dam continuing to Allagash checkpoint at Eliza Hole Rapids, approximately 3 miles upstream of the confluence with the St. John River. Length = 92 miles.

45678?

WATERS AND NAVIGABLE WATERS6 (a) FILL			
WATERS6 (a) FILL			
(a) FILL			
(a) FILL			
		Up to 1 acre waterway or wetland fill and	Greater than 1 acre waterway fill and
		secondary impacts (e.g., areas drained,	secondary impacts (e.g., areas
		flooded or cleared). Includes temporary	drained, flooded or cleared). Includes
		and permanent waterway fill.	Temporary tidal marsh impacts
		Temporary tidal marsh impacts up to 1	over 1 acre.
		acre.	Permanent tidal marsh, mudflat, or
		Permanent tidal marsh, mudflat, or	vegetated shallows 7fill over 1,000
		vegetated shallows 7 fill up to 1,000 sf.	sf.
		Proactive restoration projects with any	
		amount of impact can be reviewed under	
		Cat. II. The Corps, in consultation with	
		State and Federal agencies, must	
		determine that net adverse effects are not	
		more than minimal.	
(b) REPAIR AND Repair or m	Repair or maintenance of existing,	Repair or replacement of any non-	Replacement of non-serviceable
	currently serviceable, authorized structure	serviceable structures or fill, or repair or	structures or fill or repair or
	or fills with no substantial expansion or	maintenance of serviceable fills with	maintenance of serviceable structure
change in use.	use.	expansion of any amount up to 1 acre, or	or fill with expansion greater than 1
Work mu	 Work must be in same footprint as 	with a change in use.	acre.
original structure or	ucture or fill		

6 Navigable Waters: waters that are subject to the ebb and flow of the tide and Federally designated navigable waters (Penobscott River to Medway, Kennebec River to Moosehead Lake, and the portion of Umbagog Lake in Maine).

7 Vegetated Shallows: subtidal areas that support rooted aquatic vegetation such as eelgrass.

	CATEGORY I	CATEGORY II	INDIVIDUAL PERMIT
(c) DREDGING	Maintenance dredging of less than 1,000 cy with upland disposal. Proper siltation controls used Limited to work between November 1 and January 15. No impact to special aquatic sites8	Maintenance dredging of greater than 1,000 cy, new dredging of up to 25,000 cy, or projects that do not meet Category I. Disposal includes upland, open water or beach nourishment (above mean high water), only if material is determined suitable.	Maintenance dredging (any amount) in or affecting special aquatic sites 7. See B(a) above for dredge disposal in wetlands or water. New dredging greater than 25,000 cy or any amount in or affecting special aquatic sites 7.
(d) MOORINGS	Private, non-commercial, non-rental single boat moorings not associated with any boating facility? provided not located in a Federal Navigation Project, there is no interference with navigation, it is not located in vegetated shallows & and it is within ½ mile of the owner's residence or a public access point? Minor relocation or previously authorized mooring and moored floats consistent with Harbormaster recommendations, provided it is also consistent with local regulations, is not located in vegetated shallows, and does not interfere with navigation.	Moorings that do not meet the terms of Category I (e.g., rental or service moorings) and moorings that meet the terms of Category I that are located in a Federal anchorage.	Moorings within the horizontal limits, or with moored ve ssels that extend, into the horizontal limits of a Federal Navigation Project, except those in Federal anchorages under Category II.

8Special Aquatic Sites: include wetlands and salt marsh, mudflats, riffles and pools, and vegetated shallows.

? Boating Facilities: facilities that provide, rent, or sell mooring space, such as marinas, yacht, clubs, boat clubs, boat yards, town facilities, dockominiums, etc.

¹⁰ Cannot be at a remote location to create a convenient transient anchorage.

	CATEGORY I	CATEGORY II	INDIVIDUAL
			PERMIT
(e) PILE- SUPPORTED STRUCTURES AND FLOATS	Reconfiguration of existing authorized docks, provided structures are not positioned over vegetated shallows 6or salt marsh and provided floats are supported off substrate at low tide. No dredging, addition slips or expansion allowed.	Private piers and floats for navigational access to waterway (seasonal and permanent).	Structures, piers or floats that extend, or with docked/moored vessels that extend, into the horizontal limits of a Federal Navigation Project. Structures, including piers and floats, associated with a new or previously unauthorized boating facility8
MISCELLANEOUS	 - Temporary buoys, markers, floats, etc., for recreational use during specific events, provided they are removed within 30 days after use is discontinued. - Coast Guard approved aids to navigation. - Oil spill clean-up temporary structures or fill. - Fish/wildlife harvesting structures/fill (as defined by 33 CFR 330, App. A-4) - Scientific measurement devices and survey activities such as exploratory drilling, surveying or sampling. - Shellfish seeding (brushing the flats) projects¹¹. - Does not include oil or gas exploration and fills for roads or construction pads. - This category excludes work in National Wildlife Refuges. 	Structures or work in or affecting tidal or navigable waters that are not defined under any or the previous headings. Includes, but is not limited to, utility lines, aerial transmission lines, pipelines, outfalls, boat ramps, bridge fills/abutments, etc Shellfish/finfish (other than Atlantic salmon), or other aquaculture facilities which are consistent with the Corps revised standard siting requirements and standard permit conditions dated 7/6/94, or as revised.	If EIS required by Corps.

¹¹ Brushing the flats: the placement of tree boughs, wooden lath structures, or small-mesh fencing on mudflats for the purpose of enhancing recruitment of softshell clams (Mya arenaria).